



Sockets for RMI Relays

ZMI 2NA – ZMI 4NA



General data

Socket Material	PA66 +GF – V2
Socket colour	RAL 7035 / Pantone 1C
Contact Material	Cu Ni
Contact surface	5µm tin plated
Terminals	8µm zinc plated steel
Terminal type	Screw cage
Screws	5µm nickel plated 8.8 steel
Screw type	M3 with combi head (slotted, Philips Gr.1, Pozi)

Ratings	10A 300VAC
UL Rating	10A x 2 or 5A x 4 @ 300VAC
Operating temp.	-25° to +70°C (-13° to +158°F)
Insulation voltage	>4kV
Creepage and Clearance	Gr.C250, VDE 0110b / 2.79
Maximum Screw torque	1.0N/m
Max Wire section	
Flex / compact wire	2 x 2.5mm ² (14AWG)
Cable End	2 x 1.5mm ² (16AWG)
Terminal Protection degree	IP 20 (EN60529)

Approvals



Ordering code 2 contacts version for RMI A 2 10 xxx with Plastic hold down spring :
 Ordering code 4 contacts version for RMI A 4 5 xxx with Plastic hold down spring :
 Ordering code 2 contacts version for RMI A 2 10 xxx with Metal hold down spring :
 Ordering code 4 contacts version for RMI A 4 5 xxx with Metal hold down spring :

ZMI2NA / ZMI4NA
 ZMI4NA
 ZMI2NA-M / ZMI4NA-M
 ZMI4NA-M

Box content: 10 sockets, 10 labels, 10 Plastic hold down springs
 Box size: (W 155 x D 165 x H 70) mm Weight: 750g
 (W 6.10 x D 6.50 x H 2.75) inches Weight: 26.45oz


Optional Accessories (to be ordered separately if required)

Metal spare hold down Spring	SZMI36M
Plastic spare hold down Spring	SZMI35
Plastic spare hold down Spring	6.73.00.61.4

Labels	6.73.00.61.3
Bridging bar	ZMI-BB
Modules	

Optional Springs for ZMI series

SZMI 36M



General data

Spring material

Stainless steel

Packaging

Box content:


1 plastic bag, 10pcs.

Weight:

~5g (0.18oz)

RoHS
COMPLIANT

SZMI 35



General data

Spring material

PA66 + GF (V0)

Spring colour

RAL 7035 / Pantone 1C

Packaging

Box content:


1 plastic bag, 10pcs.

Weight:

~20g (0.70oz)

RoHS
COMPLIANT

6.73.00.61.4



General data

Spring material

PA6 + GF (V2)

Spring colour

RAL 7035 / Pantone 1C

Packaging

Box content:

1 plastic bag, 10pcs.


Weight:

~20g (0.70oz)

RoHS
COMPLIANT

Optional sockets bridging bars

ZMI-BB



General data

Plastic insulator material	PA66 + GF (V0)
Plastic insulator colour	Black
Metal jumper	Tinned copper



Packaging

Box content:	1 plastic bag, 10pcs.
Weight:	~50g (~1.76oz)



Optional Function Modules

Modules for ZMI and ZD sockets



Approvals



General data

Module material	PA66+GF (V0)
Module colour	RAL 7035 / Pantone 1C

Packaging

Box content:	1 bag, 100pcs.
Box size:	W 160 x D 70 x H 80 mm Weight: ~350g (W 6.30 x D 2.75 x H 3.15) inches Weight: ~12.3oz

Types and electrical configurations

Diagram	Type	Description	Operating voltage	LED Colour	Ordering code		Notes	
					ZMI, ZD, ZDM Sockets	ZPD9, ZPD11		
	12	Free wheeling diode A2 +	6 / 230VDC	n.a.	MODULE12	MODULE11	Only for DC relays	
	22	Free wheeling diode A1 +	6 / 230VDC	n.a.	MODULE22	MODULE21		
	32	Free wheeling diode A2 +, with LED	6 / 24VDC	Red	MODULE32	n.a.		
			24 / 60VDC		MODULE32B			
			110 / 230VDC		MODULE32C			
			6 / 24VDC	Green**	MODULE32/G			
			24 / 60VDC		MODULE32B/G			
			110 / 230VDC		MODULE32C/G			
	42	Free wheeling diode A1 +, with LED	6 / 24VDC	Red	MODULE42			
			24 / 60VDC		MODULE42B			
			110 / 230VDC		MODULE42C			
			6 / 24VDC	Green**	MODULE42/G			
			24 / 60VDC		MODULE42B/G			
			110 / 230VDC		MODULE42C/G			
	52	RC Filter	110/240VAC	n.a.	MODULE52	MODULE51	Only for AC relays	
		RC Filter	6 / 24VAC		MODULE52B	MODULE51B		
		RC Filter	24 / 60VAC		MODULE52D	MODULE51D		
	62	Signalling LED	6 / 24V	Red	MODULE62	n.a.	Can work with AC and DC Relays	
	92		24 / 60V		MODULE62E			
	62	Signalling LED	110 / 230V	Green**	MODULE92			
			6 / 24V		MODULE62/G			
			24 / 60V		MODULE62E/G			
	92	Signalling LED	110 / 230V	Red	MODULE92/G			
			6 / 24V		MODULE62C			
			24 / 60V		MODULE62D			
	62	Signalling LED, with Varistor	110 / 230V	Green**	MODULE92C			
			6 / 24V		MODULE62C/G			
			24 / 60V		MODULE62D/G			
	92	Signalling LED, with Varistor	110 / 230V	n.a.	MODULE92C/G			
			6 / 24VAC		MODULE72			MODULE71
			115VAC		MODULE72A			MODULE71A
	72	Varistor	230VAC	n.a.	MODULE82	MODULE81		
	82							
	102	Resistor	110 / 230VAC	n.a.	MODULE102	n.a.		

** Non standard devices normally not in stock and production upon request

Installation Operations

