

RF Inductor-Wirewound

Automotive



AWS16JRF0-KIT JIS 1608 Size

Designer Kit Contents

Pulse - Std Power Part Number	L (mm)	W(mm)	T (mm)	SIZE Code (JIS/EIA)	Inductance (nH)	Tolerance (±%)	RDC(Ω) Max.	IDC(mA)Max.	Quantity
AWCS001610081N6J00	1.5	1.0	0.7	1608/0603	1.6	5	0.03	700	20
AWCS001610081N8J00	1.5	1.0	0.7	1608/0603	1.8	5	0.045	700	20
AWCS001610082N2J00	1.5	1.0	0.7	1608/0603	2.2	5	0.25	700	20
AWCS001610083N3J00	1.5	1.0	0.7	1608/0603	3.3	5	0.045	700	20
AWCS001610083N6J00	1.5	1.0	0.7	1608/0603	3.6	5	0.063	700	20
AWCS001610083N9J00	1.5	1.0	0.7	1608/0603	3.9	5	0.08	700	20
AWCS001610084N3J00	1.5	1.0	0.7	1608/0603	4.3	5	0.063	700	20
AWCS001610084N7J00	1.5	1.0	0.7	1608/0603	4.7	5	0.116	700	20
AWCS001610085N1J00	1.5	1.0	0.7	1608/0603	5.1	5	0.14	700	20
AWCS001610085N6J00	1.5	1.0	0.7	1608/0603	5.6	5	0.17	700	20
AWCS001610086N3J00	1.5	1.0	0.7	1608/0603	6.3	5	0.14	700	20
AWCS001610086N8J00	1.5	1.0	0.7	1608/0603	6.8	5	0.11	700	20
AWCS001610087N5J00	1.5	1.0	0.7	1608/0603	7.5	5	0.106	700	20
AWCS001610088N2J00	1.5	1.0	0.7	1608/0603	8.2	5	0.109	700	20
AWCS001610088N7J00	1.5	1.0	0.7	1608/0603	8.7	5	0.109	700	20
AWCS001610089N1J00	1.5	1.0	0.7	1608/0603	9.1	5	0.12	700	20
AWCS001610089N5J00	1.5	1.0	0.7	1608/0603	9.5	5	0.135	700	20
AWCS0016100810NJ00	1.5	1.0	0.7	1608/0603	10	5	0.13	700	20
AWCS0016100811NJ00	1.5	1.0	0.7	1608/0603	11	5	0.086	700	20
AWCS0016100812NJ00	1.5	1.0	0.7	1608/0603	12	5	0.13	700	20
AWCS0016100813NJ00	1.5	1.0	0.7	1608/0603	13	5	0.16	700	20
AWCS0016100815NJ00	1.5	1.0	0.7	1608/0603	15	5	0.17	700	20
AWCS0016100816NJ00	1.5	1.0	0.7	1608/0603	16	5	0.104	700	20
AWCS0016100818NJ00	1.5	1.0	0.7	1608/0603	18	5	0.17	700	20
AWCS0016100820NJ00	1.5	1.0	0.7	1608/0603	20	5	0.19	700	20
AWCS0016100822NJ00	1.5	1.0	0.7	1608/0603	22	5	0.19	700	20
AWCS0016100823NJ00	1.5	1.0	0.7	1608/0603	23	5	0.19	700	20
AWCS0016100824NJ00	1.5	1.0	0.7	1608/0603	24	5	0.135	700	20
AWCS0016100827NJ00	1.5	1.0	0.7	1608/0603	27	5	0.22	600	20
AWCS0016100830NJ00	1.5	1.0	0.7	1608/0603	30	5	0.144	600	20
AWCS0016100833NJ00	1.5	1.0	0.7	1608/0603	33	5	0.22	600	20
AWCS0016100836NJ00	1.5	1.0	0.7	1608/0603	36	5	0.25	600	20
AWCS0016100839NJ00	1.5	1.0	0.7	1608/0603	39	5	0.25	600	20
AWCS0016100843NJ00	1.5	1.0	0.7	1608/0603	43	5	0.28	600	20
AWCS0016100847NJ00	1.5	1.0	0.7	1608/0603	47	5	0.28	600	20
AWCS0016100851NJ00	1.5	1.0	0.7	1608/0603	51	5	0.31	600	20
AWCS0016100856NJ00	1.5	1.0	0.7	1608/0603	56	5	0.31	600	20
AWCS0016100868NJ00	1.5	1.0	0.7	1608/0603	68	5	0.34	600	20
AWCS0016100872NJ00	1.5	1.0	0.7	1608/0603	72	5	0.49	400	20
AWCS0016100882NJ00	1.5	1.0	0.7	1608/0603	82	5	0.54	400	20
AWCS0016100891NJ00	1.5	1.0	0.7	1608/0603	91	5	0.58	400	20
AWCS00161008R10J00	1.5	1.0	0.7	1608/0603	100	5	0.58	400	20
AWCS00161008R11J00	1.5	1.0	0.7	1608/0603	110	5	0.61	300	20
AWCS00161008R12J00	1.5	1.0	0.7	1608/0603	120	5	0.75	300	20
AWCS00161008R15J00	1.5	1.0	0.7	1608/0603	150	5	0.92	280	20
AWCS00161008R16J00	1.5	1.0	0.7	1608/0603	160	5	1.25	240	20
AWCS00161008R18J00	1.5	1.0	0.7	1608/0603	180	5	1.25	240	20
AWCS00161008R20J00	1.5	1.0	0.7	1608/0603	200	5	2.1	200	20
AWCS00161008R21J00	1.5	1.0	0.7	1608/0603	210	5	2.06	200	20
AWCS00161008R22J00	1.5	1.0	0.7	1608/0603	220	5	2.1	200	20

RF Inductor-Wirewound

Automotive



AWS16JRF0-KIT JIS 1608 Size

Designer Kit Contents

Pulse - Std Power Part Number	L (mm)	W(mm)	T (mm)	SIZE Code (JIS/EIA)	Inductance (nH)	Tolerance (±%)	RDC(Ω) Max.	IDC(mA)Max.	Quantity
AWCS00161008R24J00	1.5	1.0	0.7	1608/0603	240	5	2.2	200	20
AWCS00161008R25J00	1.5	1.0	0.7	1608/0603	250	5	3.55	120	20
AWCS00161008R27J00	1.5	1.0	0.7	1608/0603	270	5	2.8	170	20
AWCS00161008R33J00	1.5	1.0	0.7	1608/0603	330	5	3.89	100	20
AWCS00161008R39J00	1.5	1.0	0.7	1608/0603	390	5	4.35	100	20
AWCS00161008R47J00	1.5	1.0	0.7	1608/0603	470	5	4.5	100	20
AWCS00161008R56J00	1.5	1.0	0.7	1608/0603	560	5	4.7	90	20

RF Inductor-Wirewound

Automotive



AWS16JRF0-KIT JIS 1608 Size

Dimensions – Millimeters (Inches)

