



Data Sheet

Type Number 6131
Designation IEC CR 11108
System Li-Manganese dioxide / Organic Electrolyte

UL Recognition:..... MH 13654 (N)
Nominal Voltage 3 V
Typical Capacity C 170 mAh
 Load 5.6 kOhm, at 20°C down to 2.0 V



Weight (approx.) 3 g
Volume 1,1 ccm
Coding..... TBA



Temperature Ranges
 Storage min -55°C max. 70°C
 Discharge min -20°C max. 65°C

Dimensions
 Diameter (A) min 11,4 max. 11,6
 Height (B) min 10,4 max. 10,8
 Shoulder Diameter[E]..... 7,8
 Shoulder Height [C]..... 0,4

Segment Electronic

Main Applications Photo
 Electronic

Typical Capacities (at 20°C)

Discharge Type	Load	End Voltage:	2.0 V
Continuous	5600 Ω	Time:	335 h
24h/d, 7d/w		Capacity [mAh]:	170
Current [μA]:		Energy [mWh]:	475

All Data contained herein is for single cells

For battery applications, performance data may vary from single cell data, depending on specific battery configuration

VARTA Microbattery GmbH, Daimlerstr. 1, D-73479 Ellwangen/Jagst
 Tel.: (+49) 7961/921-0, Telefax: (+49) 7961/921-553

Subject to change without prior notice!
 Date of issue:2004-12-16