





PRODUCT NUMBER	PITCH
OQxx32x100J0G	3.81 mm



SECTION P-P



RECOMMENDED P.C.B LAYOUT

Material:

- Item ① Male contact pin: Copper , Tin plated
- Item ② Terminal housing: Thermoplastic (UL94V-0)

Electrical:

- Voltage rating: 300V/300V
- Current rating: 10A/10.5A
- Withstanding Voltage: 1.6 KV/2.5KV
- Operating temperature: -40°C to +115°C
- Soldering temperature: 260°C±5°C/5 Sec
- Safety Approval: cULus /VDE

DIMENSION

Dim A	(N-1)×3.81+5.0
Dim B&C	(N-1)×3.81

N= number of poles

Poles	Tolerance
2P-6P	±0.15
7P-12P	±0.20
13P-18P	±0.25
19P-24P	±0.30

PART NO.: OQ xx 3 2 x 1 00J0 G

No. of poles	Body Color	RoHS compliant (lead<4%) In copper Alloy
02 2 poles	0 Black (RAL9005)	
03 3 poles	2 Red (RAL3001/D)	
...	3 Orange(RAL2011/P)	
...	4 Yellow(RAL1018/A)	
24 24 poles	5 Green(RAL6018/T)	
	6 Blue (RAL5015/A)	
	8 Grey(RAL7035/D)	
	9 White(RAL1102)	
	C Green(RAL6018/U)	

mat'l. code				surface	tolerance	projection	product family		
ltr	ecn	no	dr	date	ASME Y14.5	ASME Y14.5	TERMINAL BLOCK		
					tolerances unless otherwise specified		title		
					angles	X.±0.5	TERMINAL BLOCK		
					φ	X.X±0.3	PLUGGABLE SOCKET, RIGHT ANGLE		
					X'±1°	X.XX±0.1	scale		
					dr	HANKE FENG 032714	dwg no		
					enr	HANKE FENG 032714	sheet 1 of 1 size		
					chr	SHI JUN 032714	OQxx32x100J0G		
					appd	SHI JUN 032714	A4		
sheet index				revision	A		type		
				sheet	1		CUSTOMER Drawing		