

LVR025K-2 Product Details



LVR025K-2

TE Internal Number: F27075-000

 [Active](#)

PolySwitch Resettable Devices

[Always EU RoHS/ELV Compliant](#) ([Statement of Compliance](#))

Product Highlights:

- Radial Application
- Family Name = LVR
- Radial Construction, Through Hole Construction
- IH (Room Temperature) = .25 Amps.
- IT (Room Temperature) = .56 Amps.

[View all Features](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

 [Add to My Part List](#)

 [Request Sample](#)

 [Find Similar Products](#)

 [Buy Product](#)

Documentation & Additional Information

Product Drawings:

- [LVR025K](#) (PDF, English)

Catalog Pages/Data Sheets:

- None Available

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files:

- None Available

Additional Information:

- [Product Line Information](#)

Related Products:

- [Tooling](#)

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- UL Recognized = File No. E74889
- CSA File No. = 78165C

Electrical Characteristics:

- [IH \(Room Temperature\) \(Amps.\)](#) = 0.25
- [IT \(Room Temperature\) \(Amps.\)](#) = 0.56
- [Vmax Operating \(V\)](#) = 240
- [Rmin \(?\)](#) = 1.30
- [Rmax \(?\)](#) = 2.100
- [R1 Max \[Post Trip\] \(?\)](#) = 3.80
- Power Dissipation (Typical) (W) = 1.50

Termination Related Features:

- Construction = Radial, Through Hole

Body Related Features:

- Lead Type = Kinked

Contact Related Features:

- Family Name = LVR

Configuration Related Features:

- Coating = Coated

Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Always was RoHS compliant
- TUV Certificate No. = R72041437

Conditions for Usage:

- [Operating Temperature \(Max.\) \(°C\)](#) = 85

Operation/Application:

- Application = Radial

Packaging Related Features:

- Packaging Method = Tape & Reel

Other:

- Brand = Raychem