



Application

- Line Voltage Power Supply
- Transformer and Appliances

**RoHS
Compliant**

Features

- Low hold current
- Solid state
- Radial leaded product ideal for up to 330V AC/DC
- TUV Approved

Specifications

Operation Current	: 0.05A to 2A
Maximum Operating Voltage	: 277V AC
Maximum Interrupt Voltage	: 305V AC
Temperature Range	: -20°C to +85°C

Electrical Characteristics (23°C)

Part Number	Hold Current	Trip Current	Max.Time to Trip	Max. Current	Rated Voltage	Max. Int. Voltage	Typ. Power	Resistance	
								R _{MIN}	R _{1MAX}
	I _H , A	I _T , A	at 5X I _H , S	I _{MAX} , A	V _{MAX} , VAC	V _{I-MAX} , VAC	P _d , W	Ω	Ω
MCFRV005-277F	0.05	0.2	18	1	277	305	0.7	8	26
MCFRV008-277F	0.08	0.26	18	1.2			0.8	4.5	18
MCFRV012-277F	0.12	0.3	18	1.2			1	3	12
MCFRV016-277F	0.16	0.37	18	1.6			1.4	2.3	8
MCFRV025-277F	0.25	0.56	18.5	2.5			1.5	1.3	4.3
MCFRV033-277F	0.33	0.74	21	3.3			1.7	0.94	3.1
MCFRV040-277F	0.4	0.9	24	4			2	0.81	2.7
MCFRV055-277F	0.55	1.25	26	5.5			2.4	0.63	2.1
MCFRV075-277F	0.75	1.5	18	7.5			2.6	0.43	1.4
MCFRV100-277F	1	2	21	10			2.9	0.32	1.1
MCFRV125-277F	1.25	2.5	23	12.5			3.3	0.24	0.8
MCFRV150-277F	1.5	3	23	15			3.7	0.14	0.48
MCFRV200-277F	2	4	28	20			4.5	0.09	0.29

I_H=Hold current-maximum current at which the device will not trip at 23°C still air.

I_T=Trip current-minimum current at which the device will always trip at 23°C still air.

V_{Max.}=Maximum voltage device can withstand without damage at its rated current.

I_{Max.}= Maximum fault current device can withstand without damage at rated voltage (V_{Max.}).

P_d=Typical power dissipated from device when in tripped state in 23°C still air environment.

R_{Min.}=Minimum device resistance at 23°C.

R_{1Max.}=Maximum device resistance at 23°C, 1 hour after tripping.

Physical specifications:

Lead material: MCFRV005-277F~MCFRV016-277F Tin plated copper, 24AWG.

MCFRV025-277F~MCFRV040-277F Tin plated copper, 22AWG.

MCFRV055-277F~MCFRV200-277F Tin plated copper, 20AWG.

Soldering characteristics: MIL-STD-202, Method 208E.

Insulating coating: Flame retardant epoxy, meets UL-94V-0 requirement.

Radial Leaded PTC Resettable Fuses **multicomp**PRO

Production Dimensions




Fig.1
Lead Size: 24AWG
Φ 0.51 mm Diameter




Fig.2
Lead Size: 24AWG
Φ 0.51 mm Diameter




Fig.3
Lead Size: 22AWG
Φ 0.65 mm Diameter




Fig.4
Lead Size: 20AWG
Φ 0.81 mm Diameter





Fig.5
Lead Size: 20AWG
Φ 0.81 mm Diameter

Part Number	Figure	A	B	C	D	E	F
		Maximum	Maximum	Typical	Minimum	Maximum	Typical
MCFRV005-277F	1	7.4	12.7	5.1	7.6	3.8	1.6
MCFRV008-277F	2	7.4	12.2	5.1		3.8	1.6
MCFRV012-277F	2	8.1	12.8	5.1		3.8	1.6
MCFRV016-277F	2	7.4	14.2	5.1		3.8	1.6
MCFRV025-277F	3	8.9	15.2	5.1		3.8	1.8
MCFRV033-277F	3	12.6	15.5	5.1		3.8	1.8
MCFRV040-277F	3	12.6	15.5	5.1		3.8	1.8
MCFRV055-277F	4	12.6	16.5	5.1		4.1	1.9
MCFRV075-277F	4	15.8	20	5.1		4.8	1.9
MCFRV100-277F	4	16.3	21.7	10.2		5.1	1.9
MCFRV125-277F	5	18.8	24.5	10.2		5.3	1.9
MCFRV150-277F	5	23.8	28.3	10.2		5.3	1.9
MCFRV200-277F	4	25.2	30.6	10.2		6.1	1.9

Dimensions : Millimetres


Radial Leaded PTC Resettable Fuses **multicomp**PRO

Thermal Derating Curve



Typical Time-To-Trip at 23°C

A = MCFRV005-277F
 B = MCFRV008-277F
 C = MCFRV012-277F
 D = MCFRV016-277F
 E = MCFRV025-277F
 F = MCFRV033-277F
 G = MCFRV040-277F
 H = MCFRV055-277F
 I = MCFRV075-277F
 J = MCFRV100-277F
 K = MCFRV125-277F
 L = MCFRV150-277F
 M = MCFRV200-277F



Part Number Table

Description	UL Approval	Holding Current	Trip Current	Part Number
Radial Leaded PTC Resettable Fuse, 277V AC	No	0.05A	0.2A	MCFRV005-277F
		0.08A	0.26A	MCFRV008-277F
		0.12A	0.3A	MCFRV012-277F
		0.16A	0.37A	MCFRV016-277F
		0.25A	0.56A	MCFRV025-277F
		0.33A	0.74A	MCFRV033-277F
	Yes	0.4A	0.9A	MCFRV040-277F
		0.55A	1.25A	MCFRV055-277F
		0.75A	1.5A	MCFRV075-277F
	No	1A	2A	MCFRV100-277F
	Yes	1.25A	2.5A	MCFRV125-277F
		1.5A	3A	MCFRV150-277F
		2A	4A	MCFRV200-277F

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.