

 Live Product Chat US Only
8:30am - 5pm ET, Mon - Fri



Always EU RoHS/ELV Compliant (Statement of Compliance)

- ? Receptacle
- ? Tab Fit = 4.75 x 0.81 mm
- ? Board Mount = No
- ? Receptacle Style = Straight
- ? Insulation Support

[View all Features](#) | [Find Similar Products](#)

[Check Pricing & Availability](#)
[Search for Tooling](#)
[Product Feature Selector](#)
[Contact Us About This Product](#)

Product Drawings:

[RECEPTACLE, LIF, FASTON, 4.75 \[187\] SERIES](#) (PDF, English)

Catalog Pages/Data Sheets:

? None Available

Product Specifications:

? None Available

Application Specifications:

? [FASTON Straight Receptacles with "F" -" Crimp Feature" \(PDF, English\)](#)

? [Wire Preparation And Crimp Inspection Guide \(PDF, English\)](#)

Instruction Sheets:

? None Available

CAD Files:

? None Available

List all Documents

Additional Information:

? Product Line Information

Related Products:

? Tooling

Product Type Features:

? Product Type = Receptacle
 ? Tab Fit (mm [in]) = 4.75 x 0.81 [.187 x .032]
 ? Receptacle Style = Straight
 ? Insulation Support = Insulation Support
 ? Wire/Cable Type = Stranded
 ? Insulation Diameter (mm [in]) = 2.29 - 3.30
 [.090 - .130]
 ? Insertion Force = Low
 ? Material = Brass
 ? Finish = Tin
 ? Crimp Type = "F"
 ? CSA Certified = Yes
 ? Comment = Stress Relieved.

Mechanical Attachment:

? Board Mount = No

Body Related Features:

? Weld Tab = Without
 ? Wire Range (mm [AWG]) = 0.50 - 1.40 ² [20-16]
 ? UL Rating = Listed
 ? Stock Thickness (mm [in]) = 0.30 [0.012]

Industry Standards:

- ? RoHS/ELV Compliance = RoHS compliant, ELV compliant
- ? Lead Free Solder Processes = Not relevant for lead free process
- ? RoHS/ELV Compliance History = Always was RoHS compliant

Packaging Related Features:

? Packaging Method = Strip

Other:

? For Hermetic Header Tab = No

? Line = Premier

? Brand = AMP