






PRODUCT NUMBER

PITCH

TSxx51xB00J0G

5.08 mm



Material

- Item@Clamp: Brass(CuZn), Ni plating
- Item@Terminal screw: Steel Zinc plating "-" slot type
- Item@Female contact: PhBz, Tin plated
- Item@Top body: Thermoplastic (UL94V-0)
- Item@Bottom body: Thermoplastic (UL94V-0)

Electrical cULus/VDE/TUV

- Voltage rating: 300VAC/300VAC/300VAC
- Current rating: 15A/17A/15A
- Wire range: 2.5mm²/0.34-2.5mm²
- Solid wire(AWG): 12-24
- Stranded wire(AWG): 12-24
- Torque: 3.5Lb-In./0.5Nm/0.4Nm
- Screw: M3
- Wire strip length: 6-7mm
- Withstanding Voltage: 1.6KV/2.5KV/2.5KV
- Operating temperature: -40°C to +115°C
- Safety approval:   

N = Number of poles
 Dim A=Nx5.08
 Dim B=(N-1)x5.08
 Dim C=(N-1)x5.08

poles	Tolerance
2-6p	±0.15
7-12p	±0.25
13-18p	±0.30
19-24p	±0.40

PART NO.: TS xx 51 x B 00J0 G

Solid block	No. of poles	Color	RoHS compliant (lead<4%) In copper Alloy
0	2	Black (RAL9005)	
2	3	Red (RAL3001/D)	
3	4	Orange(RAL2011/P)	
4	5	Yellow(RAL1018/A)	
5	6	Green(RAL6018/T)	
6	8	Blue (RAL5015/A)	
8	9	Grey(RAL7035/D)	
9	9	White(RAL1102)	
C		Green(RAL6018/U)	

mat'l. code				surface ASME Y14.5	tolerance ASME Y14.5	projection 	product family TERMINAL BLOCK
ltr	ecn	no	dr	date	tolerances unless otherwise specified	MM	title
					angles X±0.5		TERMINAL BLOCK
					parallel X.X±0.3		PLUGGABLE PLUG,HOOK ON BACK SIDE,WITHOUT FLANGE
					perpendicular X.XX±0.1	scale	dwg no
					dr EVIN ZHONG 041914		sheet 1 of 1 size
					enrg EVIN ZHONG 041914		TSxx51xB00J0G A4
					chr HANKE FENG 041914		type
					appd SHI JUN 041914		CUSTOMER Drawing
sheet index	revision	sheet	A				
		1					