

HIOKI

PRECISION BATTERY TESTER BT6065, BT6075

NEW

High capacity & low internal-resistance

*Super fast charging
for EV*

*Super large cells
for ESS*



Introducing the industry's most precise battery tester Ideal for cell grading

Max. AC-IR resolution **0.01 $\mu\Omega$ 5-1/2 digit**

Max. DCV resolution **1 μV 7-1/2 digit**

Max. Ω and V test speed **12 ms**



The precision battery tester BT6075 and BT6065 are designed for OCV/AC-IR testing of high-capacity EV battery cells with low internal resistance. The extremely high resolution enables these models to perform advance cell-grading. These testers powerfully facilitate the creation of reliable and efficient OCV/IR testing systems with their innovative features and capability of high-speed testing.



High-precision grading of high-capacity batteries


Next-gen battery testing









Measurement targets

High-capacity battery cells with extremely low internal resistance are important for electric vehicles (EVs) compatible with rapid charging and stationary energy storage systems (ESSs) that are low in loss.

High-precision battery testers play an essential role in precise cell testing to maximize battery pack performance and battery cell production.



Features

- 
Industry's most accurate & high-speed OCV/IR test performance
- 
Shorter testing times while maintaining exceptional reproducibility
- 
Two testers work in tandem without interference
- 
Channel-specific correction and optional multiplexer
- 
Supports seamless setup of inspection systems
- 
High durability and long-term stable system operation

Top-tier battery measurement performance

Highest precision

Choose from 2 models depending on your testing process



Beginning- and end-of-line (BOL, EOL) test
For high-precision cell grading

BT6075

- Voltage display: 7-1/2 digits
- Max. DCV resolution: 1 μ V
- Max. AC-IR resolution: 0.01 μ Ω


In-line test of formation and aging process
OCV/AC-IR test for cell screening

BT6065

- Voltage display: 6-1/2 digits
- Max. DCV resolution: 10 μ V
- Max. AC-IR resolution: 0.01 μ Ω

Exceptional reproducibility for AC-IR and DCV measurements


Excellent resistance measurement resolution and accuracy



BT6075	$\pm 0.08\%$ rdg. $\pm 0.08 \mu\Omega$ (measurement current: 300 mA)
BT6065	$\pm 0.08\%$ rdg. $\pm 0.5 \mu\Omega$ (measurement current: 100 mA)

AC-IR offers a 10 n Ω resolution.
At a measurement current of 300 mA, stable measurement data is obtained with an excellent SN ratio suitable for inspecting low-resistance batteries.

Voltage measurement accuracy comparable to a high-precision voltmeter




BT6075	$\pm 0.0012\%$ rdg. $\pm 11 \mu$ V
BT6065	$\pm 0.002\%$ rdg. $\pm 20 \mu$ V

No additional voltmeter is needed for OCV/IR testing. Both models, one with 7-1/2 digits (resolution of 1 μ V) and the other with 6-1/2 digits (resolution of 10 μ V), feature unparalleled measurement accuracy.

Truly simultaneous Ω /V measurement

Fast testing without sacrificing precision

Simultaneously measure resistance and voltage with 1 instrument



6 sampling time settings

Measurement function	FAST1	FAST2	MEDIUM1	MEDIUM2	SLOW1	SLOW2
Ω	50 Hz	4 ms	10 ms	20 ms	40 ms	100 ms
V	60 Hz	17 ms	33 ms	100 ms	200 ms	200 ms

The BT6065 and BT6075 deliver high-speed measurement that goes beyond conventional battery testers. With two A/D converters, the instruments can perform simultaneous resistance and voltage measurement in as little as 12 ms. As a result, they can be used to build systems that deliver both testing efficiency and precision.


“We want to perform testing efficiently with two instruments.”

Stable measurement with the MIR mode (mutual interference reduction)

Ordinarily, mutual interference causes measured values to fluctuate when making simultaneous measurements with two battery testers placed in close proximity. The MIR mode reduces mutual interference to ensure stable measurement. The feature makes possible accurate, high-speed parallel-testing with two testers.

Mutual interference reduction (MIR) technology features

- No need for additional accessories like sync cables
- Unlike an older technology known as pulse output functionality, the MIR mode facilitates reliable parallel testing.



Delivers easy, reliable parallel-testing


“We want to measure numerous channels accurately.”

Compensation of individual channels with referential adjustment

When measuring rows of batteries in a tray, eddy currents occurring in the metal enclosures of adjacent batteries cause measurement error. The referential adjustment function, which accurately compensates for the effects of eddy currents by using actual batteries as a reference, allows more accurate measurement.

Referential adjustment features

- Referential adjustment: up to 528 channels
- Adjustment data for up to six batteries (6 × 528 channels) can be saved on the instrument using its “panel save” feature.



Accurately compensating for the effects of eddy currents caused by adjacent batteries

“We’re concerned about abrupt system stoppages.”

Significantly improving route resistance tolerance

Route resistance refers to the total value of wiring resistance and probe contact resistance in a given testing system. Since the BT6065/BT6075 has high route resistance tolerance, it provides high durability in the face of probe deterioration and increased relay contact resistance. This prevents abrupt testing system stoppages while improving up-time.

Route resistance tolerance

- 10 Ω: with measurement current of 300 mA (3 mΩ range only)
- 50 Ω: with measurement current of 100 mA or less (all ranges)



Improving the long-term reliability of testing systems


“We want to replace probes less frequently.”

Continuously monitoring for errors with the route resistance monitor

The route resistance monitor displays individual wiring route resistance values for 4-terminal measurement. This feature lets you continuously watch for wiring errors like probe wear and wire breaks. The feature can predict maintenance needs and lower operating costs by helping you make numerically-based decisions as to which probe needs to be replaced.

Route resistance monitor features

- Dual threshold settings (WARNING, FAIL)
- Improved testing reliability by simultaneously measuring route resistance for Ω and V



Monitoring route resistance and displaying a warning before a measurement error occurs

Standard functions



A resistive touch panel lets you operate the instrument precisely, even if you're wearing gloves.

AC four-terminal method

Resistance measurement, which is performed using the AC 4-terminal method at 1 kHz, is not affected by factors such as wiring resistance.

Comparator capability

The instrument's comparator judges resistance and DC voltage values, generating three possible results (Hi, IN, Lo).

Saving measurement conditions

Save and load up to six sets of measurement conditions, including referential adjustment values.

Averaging measured values

Minimal variability by averaging from 1 to 256 measured values makes measurement stable.

Temperature input (temp. sensor terminal)


The optional Temperature Sensor Z2005 can be used to measure ambient temperature.

Self-calibration (resistance and DC voltage)

Maintain high precision by correcting for gain fluctuations and minuscule drift in internal measurement circuitry.


Seamless system integration

Boosting testing systems' durability




Function for displaying the wiring's reactance X and impedance Z

The instruments provide an advanced mode that can display reactance X and impedance Z. This capability is useful when troubleshooting issues at system startup and when optimizing wiring layouts.



Loops increase the effects of induction flux caused by eddy currents, mutual interference, and peripheral equipment.




A more robust system can be attained by routing wires so as to minimize X values.



Command compatibility mode

Communication commands from the previous BT3562A model can be used without modification. As a result, you can replace just the battery testers and verify proper operation of newly installed equipment right away.



Ext. I/O monitor

In addition to checking EXT. I/O input signals on the screen, you can turn output signals on and off as desired. This capability also simplifies verification of PLC programming.



Commands monitor

Display communications data (received commands and sent data) on the screen. This capability is useful when checking PLC programming.

Options

Dedicated multiplexer optimized for high-speed, high-precision measurement


Hioki's multiplexer can also be zero-adjusted, resulting in a more accurate system that corrects the effects of eddy currents.




Switch Mainframe SW1002

Example setup using the SW1002

AC-IR measurement (1 kHz), OCV measurement, up to 132 channels



Measurement time



$$\text{Cycle time} = (\text{Communication time} + \text{Channel switching time} + \text{Measurement response time} + \text{Sampling time}) \times \text{Number of channels}$$

Instrument	Function	Measurement speed	Number of channels	Measurement response time (delay time)	Switched measurement time (all channels)	Conditions
BT6065 BT6075	ΩV	FAST1 (4 ms)	11	8 ms	0.26 s (approx. 23 ms/channel)	<ul style="list-style-type: none"> Communication with BT6065 via LAN After normal reset Fixed range Manual DCV calibration performed before measurement External trigger Trigger reception relay mode off
		MEDIUM2 (33 ms, 60 Hz)	11	8 ms	0.58 s (approx. 52 ms/channel)	
		SLOW2 (200 ms)	11	8 ms	2.5 s (approx. 227 ms/channel)	

The measurement times presented above are examples for reference. The times can change based on many factors such as communication methods. For more information about how the measurement accuracy for each measurement range is affected when the Precision Battery Testers are used in combination with the multiplexer, see "Effects of using the instrument with the SW9001."

Multiplexer specifications

Switch Mainframe SW1001, SW1002

Number of slots	3 slots (SW1001) 12 slots (SW1002)
Supported BT6065/ BT6075 module	Multiplexer Module SW9001 (2-wire, 4-wire)
Max. input voltage	DC 60 V, AC 30 V rms, 42.4 V peak
Interfaces	LAB, USB, RS-232C (host), RS-232C (command transfer function)
EXT. I/O	SCAN input, SCAN_RESET input, CLOSE output (scan control)

Multiplexer Module SW9001

Wiring method	2-wire or 4-wire
Number of channels	22 channels (2-wire method) or 11 channels (4-wire method)
Contact method	Mechanical relay
Channel switching time	11 ms (not including measurement time)
Max. allowable voltage	DC 60 V, AC 30 V rms, 42.4 V peak
Max. allowable current	DC 1 A, AC 1 A rms
Connectors used	D-sub 50-pin pin header

Effects of using the instrument with the SW9001¹⁾

Range	Effect
R 3 mΩ (300 mA)	0.1% f.s.
R 3 mΩ (100 mA)	0.1% f.s.
R 30 mΩ	0.03% f.s.
R 300 mΩ	0.03% f.s.
R 3 Ω	0.03% f.s.
R 30 Ω	0.03% f.s.
All V ranges	5 μV

30 Ω range: source contact check operation not available

¹⁾ Effect before zero adjustment


Appearance



Interfaces

EXT. I/O RS-232C LAN USB

- 1 Power inlet
- 2 Ext. I/O connector
- 3 Ext. I/O mode switch
- 4 Power switch
- 5 RS-232C connector
- 6 LAN connector
- 7 Type-C USB connector
- 8 Temp. sensor terminal



Specifications

General specifications		Accuracy guaranteed: 1 year
Operating temperature and humidity range	0°C to 40°C (32°F to 104°F), 80% RH or less (non-condensing)	
Standard compliance	Safety: EN 61010 EMC: EN 61326 Class A	
Power supply	Rated supply voltage: 100 V to 240 V AC (assuming voltage fluctuations of $\pm 10\%$ of the rated supply voltage) Rated power supply frequency: 50 Hz, 60 Hz Maximum rated power: 40 VA	
Interfaces	LAN (10BASE-T/100BASE-T, TCP/IP) USB (COM mode, C-type receptacle) USB (MEM mode ^{*1} , A-type receptacle, for Z4006 USB Drive) RS-232C (9600 bps, 19200 bps, 38400 bps) EXT. I/O	
Dimensions and weight	Approx. 215W \times 88H \times 313D mm (8.5W \times 3.5H \times 12.3D in.) (excluding protruding parts) Approx. 3.1 kg (6.8 lb.)	
Included accessories	Power cord \times 1, Startup Guide \times 1, Operating Precautions \times 1	

*1. Only screenshots can be saved.

Basic specifications

Measurement range	<ul style="list-style-type: none"> Resistance ranges: 3 mΩ, 30 mΩ, 300 mΩ, 3 Ω, 30 Ω Voltage ranges: 10 V, 100 V 							
Measurement functions	Ω V, Ω , V							
DC input resistance (10 V range)	Measurement functions	10 M Ω	HIGH Z					
	Ω V/ Ω	10 M Ω $\pm 10\%$	1 G Ω or greater					
	V	10 M Ω $\pm 10\%$	10 G Ω or greater					
	(Fixed at 10 M Ω setting when using the 100 V range)							
Max. input voltage	DC ± 120 V							
Max. rated line-to-ground voltage	DC ± 120 V							
Sampling time	Measurement function	FAST1	FAST2	MEDIUM1 (MED1)	MEDIUM2 (MED2)	SLOW1	SLOW2	
				Ω	20 ms			40 ms
	Ω	50 Hz	4 ms	10 ms	17 ms	33 ms	100 ms	200 ms
		60 Hz	4 ms	10 ms	17 ms	33 ms		
	V	50 Hz	4 ms	10 ms	20 ms	40 ms	100 ms	200 ms
		60 Hz	4 ms	10 ms	17 ms	33 ms		
Temperature measurement: approx. 2 s								
Time added for MIR resistance measurement	With resistance measurement MIR mode enabled: 6 ms to 12 ms							
Response time	Approx. 8 ms (when measuring only resistance and voltage of a 4 V battery)							
Accuracy guarantee conditions	Accuracy guaranteed temperature and humidity range: 23°C $\pm 5^\circ\text{C}$ (73°F $\pm 9^\circ\text{F}$), 80% RH or less Warm-up time: 60 min. or more Resistance self-calibration: performed after warm-up time DC voltage self-calibration: performed after warm-up time Adjustment processing <ul style="list-style-type: none"> Resistance measurement: after zero adjustment or after referential adjustment is enabled DC voltage measurement: after zero adjustment 							
Functions	Averaging (up to 256 times), contact check, resistance self-calibration, DC voltage self-calibration, zero adjustment (528 channels), referential adjustment (528 channels), route resistance monitor, resistance measurement MIR mode, comparator, command compatibility (BT3562A Battery HiTester compatible), panel save (number of savable sets: 6), command monitor, EXT. I/O test							

Resistance measurement accuracy

		Range (measurement current) ^{*1}					
		3 m Ω (300 mA)	3 m Ω (100 mA)	30 m Ω (100 mA)	300 m Ω (10 mA)	3 Ω (1 mA)	30 Ω (100 μA)
SLOW2 (sampling speed)	OFF	$\pm 0.08\%$ rdg.				$\pm 0.10\%$ rdg.	$\pm 0.15\%$ rdg.
	ON	$\pm 0.1 \mu\Omega$	$\pm 0.5 \mu\Omega$	$\pm 1 \mu\Omega$	$\pm 10 \mu\Omega$	$\pm 100 \mu\Omega$	$\pm 1 \text{ m}\Omega$
HIGH RESOLUTION	OFF	$\pm 0.08 \mu\Omega$	$\pm 0.50 \mu\Omega$	$\pm 0.5 \mu\Omega$	$\pm 5 \mu\Omega$	$\pm 50 \mu\Omega$	$\pm 0.5 \text{ m}\Omega$
Max. display value	OFF	5.1000 m Ω	5.1000 m Ω	51.000 m Ω	510.00 m Ω	5.1000 Ω	51.000 Ω
	ON	5.10000 m Ω	5.10000 m Ω	51.00000 m Ω	510.0000 m Ω	5.10000 Ω	51.00000 Ω
Resolution	OFF	0.1 $\mu\Omega$	0.1 $\mu\Omega$	1 $\mu\Omega$	10 $\mu\Omega$	100 $\mu\Omega$	1 m Ω
	ON	0.01 $\mu\Omega$	0.01 $\mu\Omega$	0.1 $\mu\Omega$	1 $\mu\Omega$	10 $\mu\Omega$	100 $\mu\Omega$
Measurement current frequency	1 kHz ± 0.2 Hz						

*1. Rms value, measurement current error within $\pm 10\%$

Additional accuracy deterioration

Temperature coefficient: add the following value to the measurement accuracy if the temperature is 0°C to 18°C or 28°C to 40°C: (measurement accuracy $\times 0.1$) / °C
 Addition when resistance measurement MIR mode is enabled: add $\pm 0.01\%$ rdg. to the resistance measurement accuracy.

DC voltage measurement accuracy

		Range	
		10 V	100 V
SLOW2 (sampling speed)	OFF	$\pm 0.002\%$ rdg. $\pm 20 \mu\text{V}$	$\pm 0.004\%$ rdg. $\pm 0.6 \text{ mV}$
	ON	$\pm 0.002\%$ rdg. $\pm 20 \mu\text{V}$	$\pm 0.004\%$ rdg. $\pm 0.6 \text{ mV}$
Max. display value	± 12.00000 V		± 120.0000 V
Resolution	10 μV		100 μV

BT6075

		Range	
		10 V	100 V
SLOW2 (sampling speed)	OFF	$\pm 0.0012\%$ rdg. $\pm 11 \mu\text{V}$	$\pm 0.003\%$ rdg. $\pm 0.60 \text{ mV}$
	ON	$\pm 0.0012\%$ rdg. $\pm 11 \mu\text{V}$	$\pm 0.003\%$ rdg. $\pm 0.60 \text{ mV}$
Max. display value	± 12.000000 V		± 120.00000 V
Resolution	1 μV		10 μV

Additional accuracy deterioration

Temperature coefficient: add the following value to the measurement accuracy if the temperature is 0°C to 18°C or 28°C to 40°C: (measurement accuracy $\times 0.1$) / °C

Temperature measurement accuracy

Range	-10.0°C to 60.0°C (14°F to 140°F)
Accuracy (instrument + Z2005)	$\pm 0.5^\circ\text{C}$ (measurement temperature of 10.0°C to 40.0°C) $\pm 1.0^\circ\text{C}$ (measurement temperature of -10.0°C to 9.9°C, 40.1°C to 60.0°C)

Route resistance measurement accuracy

Resistance range	3 m Ω	30 m Ω	300 m Ω	3 Ω	30 Ω
Measurement current	300 mA	100 mA	100 mA	10 mA	1 mA
Accuracy	3.0% rdg. $\pm 0.5 \Omega$ (3 m Ω , 30 m Ω , 300 m Ω , or 3 Ω resistance range) 3.0% rdg. $\pm 3 \Omega$ (30 Ω resistance range)				
Max. display value	10.0 Ω	50.0 Ω	50.0 Ω	50.0 Ω	500 Ω
Route resistance resolution	0.1 Ω	0.1 Ω	0.1 Ω	0.1 Ω	1 Ω

Options

Test leads

NEW PIN TYPE LEAD L2120

Rated voltage: 1000 V DC
 Rated current: 2 A DC
 Approx. length:
 L: 1.4 m (4.6 ft.)
 A: 300 mm (11.8 in.)
 B: 172 mm (6.8 in.)




NEW CLIP TYPE LEAD L2121

Rated voltage: 60 V DC
 Rated current: 2 A DC
 Approx. length:
 L: 1.2 m (3.9 ft.)
 A: 130 mm (5.1 in.)
 B: 83 mm (3.3 in.)




PIN TYPE LEAD L2100

Rated voltage: 1000 V DC
 Rated current: 2 A DC
 Approx. length:
 L: 1.4 m (4.6 ft.)
 A: 300 mm (11.8 in.)
 B: 172 mm (6.8 in.)



Test leads featuring a new design that minimizes the effects of eddy currents

Internal twisted-pair wiring right up to the tip of the test lead minimizes magnetic noise and reduces measurement variability.



Conventional test leads may also be used

Conventional test leads may also be used by changing the orientation in which the test leads are connected. Making measurements with the test leads connected improperly will not damage the instrument.



When using L2120, L2121



When using L2100

PC connectivity



RS-232C CABLE L9637
 9-pin/9-pin, 3 m (9.8 ft.)




USB CABLE L9510
 USB A-C type



USB DRIVE Z4006
 16 GB



LAN CABLE 9642
 Straight Ethernet cable, supplied with straight-to-cross conversion adapter, 5 m (16.4 ft.)



Lead length

L: overall length
 A: from junction to probe
 B: probe length


Other



TEMPERATURE SENSOR Z2005
 1 m (3.3 ft.)



0 ADJ BOARD Z5038
 For L2120, L2100



TIP PIN 9772-90
 To replace the tip on the pin-type lead L2120/L2100 (one pin)

Using multiplexers



SWITCH MAINFRAME SW1002
 12 slots, max. 132 channels (4-wire)



SWITCH MAINFRAME SW1001
 3 slots, max. 33 channels (4-wire)



MULTIPLEXER MODULE SW9001
 Max. 11 channels (4-wire), 2-wire/4-wire



CONNECTION CABLE L2108
 4-terminal banana, 0.84 m (2.8 ft.)

Note: Company names and product names appearing in this brochure are trademarks or registered trademarks of various companies.

HIOKI

HIOKI E. E. CORPORATION

HEADQUARTERS

81 Koizumi,
 Ueda, Nagano 386-1192 Japan
<https://www.hioki.com/>



Scan for all regional contact information

DISTRIBUTED BY