EM2575 Series
EuroMag Terminal Blocks
Header (Mates with EM2565, EM3108 Series); 5.08 Centers



SPECIFICATIONS
Rating: 16A, 300V
Center Spacing: 0.20" (5.08mm)
Consult factory for 0.40" (10.16mm)
Housing Material: UL rated 94V0 Thermoplastic
Contact Material: Brass Tin-Plated
Operating Temperature: 105°C (221°F) max., -40°C (-40°F) min.
Recommended PCB Hole Diameters: 0.055" (1.40mm)
Construction: Mold-to-Length
Agency Information: c UL us File E62622; CE Certified

Poles	Open L (mm)	Closed L (mm)	Poles	Open L (mm)	Closed L (mm)
2	10.16	12.08	14	71.12	73.04
3	15.24	17.16	15	76.20	78.12
4	20.32	22.24	16	81.28	83.20
5	25.40	27.32	17	86.36	88.28
6	30.48	32.40	18	91.44	93.36
7	35.56	37.48	19	96.52	98.44
8	40.64	42.66	20	101.60	103.52
9	45.72	47.64	21	106.68	105.60
10	50.80	62.72	22	111.76	113.68
11	55.88	67.80	23	116.84	118.76
12	60.96	62.88	24	121.92	123.84
13	66.04	67.96			

To convert to inches, divide by 25.4

Dimensions - mm (in)



Part Numbering System

Series	# of Poles	Orientation	Side Base
EM2575	☐☐	☐	☐
	02 to **24**	**H** - horizontal **V** - vertical	**O** - open **C** - closed

Mating Plugs: EM2565 pg. 89
EM2488 pg. 90
EM3108 pg. 91