




Features

- Miniature size
- High self-resonant frequency
- High current
- Low DCR
- High Q
- AEC-Q200 compliant
- RoHS compliant* and halogen free**

Applications

- Radio transmitters
- RF amplifiers
- Tuning applications
- High frequency applications
- Automotive systems

CW2012A Series – 0805 Chip Inductors

Electrical Specifications

Bourns Part No.	Inductance		Q	L @ Test Frequency (Hz)	Q @ Test Frequency (MHz)	SRF (MHz)	DCR (Ω)	Rated Current (mA)
	L (nH)	Tol.	Min.			Min.	Max.	Max.
CW2012A-2N0_	2.0	±0.2 nH, ±0.3 nH	70	0.1 V / 250 M	1500	8000	0.03	800
CW2012A-3N9_	3.9		70			5750	0.04	
CW2012A-4N7_	4.7		70			5750	0.04	
CW2012A-6N8_	6.8		70			5500	0.06	
CW2012A-7N5_	7.5		70			4500	0.06	
CW2012A-8N2_	8.2	±5 %, ± 10 %	70		1000	4700	0.06	600
CW2012A-10N_	10		70			4200	0.08	
CW2012A-12N_	12		80			4000	0.08	
CW2012A-15N_	15		80			3400	0.10	
CW2012A-18N_	18		80			3300	0.10	
CW2012A-22N_	22		60		2600	0.12	500	
CW2012A-24N_	24		60		2000	0.12		
CW2012A-27N_	27		60		2500	0.12		
CW2012A-33N_	33		60		2050	0.13		
CW2012A-36N_	36		65		1700	0.13		
CW2012A-39N_	39		65		2000	0.15		
CW2012A-43N_	43		65	1650	0.15			
CW2012A-47N_	47		65	1650	0.17			
CW2012A-56N_	56		65	1550	0.19			
CW2012A-68N_	68		60	1450	0.22			
CW2012A-82N_	82		55	1300	0.40	400		
CW2012A-R10_	100		55	1200	0.52			
CW2012A-R11_	110		55	1200	0.52			
CW2012A-R12_	120		50	1100	0.55			
CW2012A-R15_	150		50	920	0.73			
CW2012A-R18_	180		50	250	870	0.88	340	
CW2012A-R22_	220		50		850	1.18		
CW2012A-R24_	240		48		690	1.20		
CW2012A-R27_	270		48		650	1.36		
CW2012A-R33_	330		40		600	1.40		
CW2012A-R39_	390	25	0.1 V / 100 M	560	1.50	290		
CW2012A-R47_	470	25		0.1 V / 50 M	375	1.76	250	
CW2012A-R56_	560	23			100	340	1.90	210
CW2012A-R62_	620	23				220	2.00	105
CW2012A-R68_	680	23				200	2.15	200
CW2012A-R75_	750	20	200			2.25	185	
CW2012A-R82_	820	20	200	2.50		170		
CW2012A-1R0_	1000	15		50	100	2.60	170	

Note:

Underscore indicates Inductance Tolerance Code:

CW2012A-2N0_ ~ CW2012A-4N7_: B = ±0.2 nH, D = ±0.3 nH

CW2012A-6N8_ ~ CW2012A-1R0_: J = ±5 %, K = ±10 %



WARNING

Cancer and Reproductive Harm

www.P65Warnings.ca.gov

* RoHS Directive 2015/863, Mar 31, 2015 and Annex.

** Bourns considers a product to be "halogen free" if (a) the Bromine (Br) content is 900 ppm or less; (b) the Chlorine (Cl) content is 900 ppm or less; and (c) the total Bromine (Br) and Chlorine (Cl) content is 1500 ppm or less.

Specifications are subject to change without notice.

Users should verify actual device performance in their specific applications. The products described herein and this document are subject to specific legal disclaimers as set forth on the last page of this document, and at

www.bourns.com/docs/legal/disclaimer.pdf.

Additional Information

Click these links for more information:



[PRODUCT SELECTOR](#)

[TECHNICAL LIBRARY](#)

[INVENTORY](#)


[SAMPLES](#)

[CONTACT](#)

CWF2012A Series – 0805 Chip Inductors

BOURNS®

Product Dimensions



How to Order

Model **CW2012A - 2N0**


Inductance Value Code _____
(See Table)

Tolerance Code _____


CW2012A-2N0_ ~ CW2012A-4N7_:
B = ± 0.2 nH, D = ± 0.3 nH

CW2012A-6N8_ ~ CW2012A-1R0_:
J = ± 5 %, K = ± 10 %

Recommended Layout



Solder Profile



General Specifications

Operating Temperature
..... -55 °C to +125 °C
(Temperature rise included)

Storage Temperature
..... -55 °C to +125 °C

Rated Current
..... Inductance drops ≤ 20 %

Moisture Sensitivity Level..... 1

ESD Classification (HBM)..... N/A

Materials


Core Material..... Ceramic

Wire..... Enameled copper

Terminal..... Ag/Ni/Sn

Packaging..... 2,000 pcs. per 7" reel

Electrical Schematic



Specifications are subject to change without notice.


Users should verify actual device performance in their specific applications.

The products described herein and this document are subject to specific legal disclaimers as set forth on the last page of this document, and at www.bourns.com/docs/legal/disclaimer.pdf.

CWF2012A Series – 0805 Chip Inductors

BOURNS®

Packaging Specifications



USER DIRECTION OF FEED

QTY: 2,000 PCS. PER REEL

BOURNS®

Americas: Tel: +1 951-781-5500 • Email: americus@bourns.com

Mexico: Tel: +52-614-478-0400 • Email: mexicus@bourns.com

Asia: Tel: +886-2-2562-4117 • Email: asiacus@bourns.com

EMEA: Tel: +36 88 885 877 • Email: eurocus@bourns.com

www.bourns.com

REV. 03/25

Specifications are subject to change without notice.

Users should verify actual device performance in their specific applications.

The products described herein and this document are subject to specific legal disclaimers as set forth on the last page of this document, and at www.bourns.com/docs/legal/disclaimer.pdf.

This legal disclaimer applies to purchasers and users of Bourns® products manufactured by or on behalf of Bourns, Inc. and its affiliates (collectively, "Bourns").

Unless otherwise expressly indicated in writing, Bourns® products and data sheets relating thereto are subject to change without notice. Users should check for and obtain the latest relevant information and verify that such information is current and complete before placing orders for Bourns® products.

The characteristics and parameters of a Bourns® product set forth in its data sheet are based on laboratory conditions, and statements regarding the suitability of products for certain types of applications are based on Bourns' knowledge of typical requirements in generic applications. The characteristics and parameters of a Bourns® product in a user application may vary from the data sheet characteristics and parameters due to (i) the combination of the Bourns® product with other components in the user's application, or (ii) the environment of the user application itself. The characteristics and parameters of a Bourns® product also can and do vary in different applications and actual performance may vary over time. Users should always verify the actual performance of the Bourns® product in their specific devices and applications, and make their own independent judgments regarding the amount of additional test margin to design into their device or application to compensate for differences between laboratory and real world conditions.

Unless Bourns has explicitly designated an individual Bourns® product as meeting the requirements of a particular industry standard (e.g., IATF 16949) or a particular qualification (e.g., UL listed or recognized), Bourns is not responsible for any failure of an individual Bourns® product to meet the requirements of such industry standard or particular qualification. Users of Bourns® products are responsible for ensuring compliance with safety-related requirements and standards applicable to their devices or applications.

Bourns® products are not recommended, authorized or intended for use in nuclear, lifesaving, life-critical or life-sustaining applications, nor in any other applications where failure or malfunction may result in personal injury, death, or severe property or environmental damage. Unless expressly and specifically approved in writing by two authorized Bourns representatives on a case-by-case basis, use of any Bourns® products in such unauthorized applications might not be safe and thus is at the user's sole risk. Life-critical applications include devices identified by the U.S. Food and Drug Administration as Class III devices and generally equivalent classifications outside of the United States.

Bourns expressly identifies those Bourns® standard products that are suitable for use in automotive applications on such products' data sheets in the section entitled "Applications." Unless expressly and specifically approved in writing by two authorized Bourns representatives on a case-by-case basis, use of any other Bourns® standard products in an automotive application might not be safe and thus is not recommended, authorized or intended and is at the user's sole risk. If Bourns expressly identifies a sub-category of automotive application in the data sheet for its standard products (such as infotainment or lighting), such identification means that Bourns has reviewed its standard product and has determined that if such Bourns® standard product is considered for potential use in automotive applications, it should only be used in such sub-category of automotive applications. Any reference to Bourns® standard product in the data sheet as compliant with the AEC-Q standard or "automotive grade" does not by itself mean that Bourns has approved such product for use in an automotive application.

Bourns® standard products are not tested to comply with United States Federal Aviation Administration standards generally or any other generally equivalent governmental organization standard applicable to products designed or manufactured for use in aircraft or space applications. Bourns expressly identifies Bourns® standard products that are suitable for use in aircraft or space applications on such products' data sheets in the section entitled "Applications." Unless expressly and specifically approved in writing by two authorized Bourns representatives on a case-by-case basis, use of any other Bourns® standard product in an aircraft or space application might not be safe and thus is not recommended, authorized or intended and is at the user's sole risk.

The use and level of testing applicable to Bourns® custom products shall be negotiated on a case-by-case basis by Bourns and the user for which such Bourns® custom products are specially designed. Absent a written agreement between Bourns and the user regarding the use and level of such testing, the above provisions applicable to Bourns® standard products shall also apply to such Bourns® custom products.

Users shall not sell, transfer, export or re-export any Bourns® products or technology for use in activities which involve the design, development, production, use or stockpiling of nuclear, chemical or biological weapons or missiles, nor shall they use Bourns® products or technology in any facility which engages in activities relating to such devices. The foregoing restrictions apply to all uses and applications that violate national or international prohibitions, including embargos or international regulations. Further, Bourns® products and Bourns technology and technical data may not under any circumstance be exported or re-exported to countries subject to international sanctions or embargoes. Bourns® products may not, without prior authorization from Bourns and/or the U.S. Government, be resold, transferred, or re-exported to any party not eligible to receive U.S. commodities, software, and technical data.

To the maximum extent permitted by applicable law, Bourns disclaims (i) any and all liability for special, punitive, consequential, incidental or indirect damages or lost revenues or lost profits, and (ii) any and all implied warranties, including implied warranties of fitness for particular purpose, non-infringement and merchantability.

For your convenience, copies of this Legal Disclaimer Notice with German, Spanish, Japanese, Traditional Chinese and Simplified Chinese bilingual versions are available at:

Web Page: <http://www.bourns.com/legal/disclaimers-terms-and-policies>

PDF: <http://www.bourns.com/docs/Legal/disclaimer.pdf>