



**NOTE:**

- Electrical test:
  - 100% open short & miss wire test;
  - Insulation resistance:DC 300V 0.1S 10MΩ;
  - Conductor resistance:2Ω Max;
  - SSD TEST:1800MB/S (min)
- Feature:
  - Full-featured USB4 Type-C Cable (USB4 Gen3x2)
  - Transmission rate Up to 40Gbps
  - Resolution up to single 8k@60Hz or dual 4k@60Hz
  - Backwards compatible with USB 3.1, 3.0 and 2.0 and Thunderbolt 3
  - Supports USB power delivery 3.1 (EPR 5V/5A-20V/5A) 100W
- RoHS 2011/65/EU and amendment directives (EU) 2015/863 compliant;REACH 1907/2006/EC compliant.

**MATERIAL LIST:**

⑤	MOULDING	PVC Black	2	
④	E-mark	USB4 GEN3*2 40Gbps 100W/5A	2	
③	Housing	Aluminum housing Gold beveled highlighting	2	
②	USB TYPE C	USB 4 C/M Solder Type,Black PBT Insulation,The Pin Gold Plating, the shell for Gold Plating With E-MARK	2	
①	CABLE	USB4 GEN3*2 CABLE[32AWG BC*1P+D+AM+HM]*4C+32AWG BC*1P+32AWG BC*4C+24AWG BC*2C+D+AM+B] PVC+Gold+Black cotton braiding OD:4.8±0.2MM	1	

11.02.9039	ROLINE GOLD USB4 Gen3x2 Cable, 40Gbit/s, C-C, M/M, 100W	2000±30mm
11.02.9038	ROLINE GOLD USB4 Gen3x2 Cable, 40Gbit/s, C-C, M/M, 100W	1000±20mm
ITEM NO.	DESC.	LENGTH

NO.	PARTS NAME	SPECIFICATION DESCRIPTION	QT' Y	REMARK
		NEW	2024-01-30	AO
BY	CHK	REVISION RECORD MODIFICATIONS	DATE	REV.

