



*TC:tinned copper *D:drain *AM:aluminum foil mylar,*A:Aluminum foil *B:braid

MATERIAL LIST:

⑦	Micro B	Power input	1	
⑥	OUTER MOLD	PVC color For BLACK	1	
⑤	Housing	ABS Housing Black	3	
④	PCB	USB Signal amplifier IC	3	
③	USB A TYPE	USB A /F Solder Type,Blue PBT Insulation,The Pin Gold Plating, the shell for Nickel Plating with PCB	1	
②	USB TYPE C	USB TYPE C /M,Black PBT Insulation,The Pin Gold Plating, the shell for Nickel Plating	1	
①	CABLE	USB 3.0 (28AWG TC*1P+D+AM)*2+(28AWG TC*1P)+(24AWG TC*2C)+A+D+B(AL-MG) OD:5.5±0.2mm	1	
NO.	PARTS NAME	SPECIFICATION STANDARD	QT'Y	REMARK

		NEW	2023-03-30	A
BY	CHK	REVISION RECORD MODIFICATIONS	DATE	REV.

NOTE:

- Electrical test:
 - 100% computer+ SSD test
 - Data Transfer: Up to 5Gbps
 - Output voltages :5V DC.
 - Output current:900mA.
- Operation temperature:-10℃ ~+60℃
 Storage temperature:-20℃ ~ +80℃
 RoHS 2.0 and REACH Compliant

12.04.1068	20000±200	ROLINE Ultra Long USB3.2 Gen1 Extension Cable, C-A, M/F, 20m
ITEM NO.	Length (mm)	DESC.

SECOMP