



NOTE:

1. Electrical test:

- (1). 100% open short & miss wire test;
- (2). Insulation resistance: DC 100V 0.01S 10M ohm;
- (3). Contactor resistance: 3 ohm Max;
- (4). Mac book pro + LG Monitor TEST: 3840*2160@60Hz
- (5). Transmission rate : 20Gbps Current rate: 100W/5A

2. RoHS 2.0 and REACH COMPLIANT

3. PRINTING: E***** 兄 AWM STYLE 2725 80°C 30V VW-1 SUPER HIGH SPEED

USB Revision 3.2

MATERIAL LIST:

⑤	OUT MOLD	PVC Mouldling	2	
④	INNER MOLD	LD-PE	2	
③	E-mark	GEN2*2 20Gbps 100W/5A	1	
②	TYPE C	USB C/M Solder Type, Black PBT Insulation, The Pin Gold Plating, the shell for Nickel Plating+Iron Shield	2	
①	CABLE	USB3.2 CABLE [32AWG*1P+D+AL+MY]*4C+32AWG*1P+32AWG*4C+23AWG*4C+AB TPE/BLACK OD: 5.0±0.2mm	1	
NO.	PARTS NAME	SPECIFICATION STANDARD	QT'Y	REMARK

ITEM NO.	LENGTH
11.44.9072	1500±30MM
11.44.9073	2000±30MM

DESC.	ROLINE GREEN USB3.2 Gen 2x2 Cable, 20Gbit/s, C-C, M/M
-------	---

		NEW	2023-02-01	V0
BY	CHK	REVISION RECORD MODIFICATIONS	DATE	REV.

