


# ROLINE GREEN USB 3.2 Gen 2 Cable, PD, C-C, M/M, 4K UHD-1, 10Gbit/s, Emark, 100W, black, 1 m

<b>Product No.</b>	11.44.9057
<b>Manufacturer</b>	ROLINE GREEN
<b>Manufacturer No.</b>	11.44.9057
<b>EAN (single piece)</b>	7630049629196



**Full-featured USB 3.1 / USB 3.2 Gen 2 cable with a data transmission rate of up to 10 Gbit/s and full Power Delivery support of up to 20V 5A!**

- High quality USB 3.1 / USB 3.2 Gen 2 cable with improved shielding
- With the new reversible Type C connectors at both ends
- Gold-plated contacts for low wear at high plugging cycles
- Suitable for data transfer rates of up to 10 Gbit/s
- Supports USB Power Delivery to 20V / 5A
- Supports video transfer

**ROLINE GREEN products are marked only with a paper tag and build with halogen-free TPE material, without plastic bags and without plastic cable straps for use in eco-friendly environments.**

Note: According to the current specifications of USB.org we have adapted the technical data of our USB 3 products. The new designation for the already known USB specifications has been changed to USB 3.2 Gen 1 (formerly USB 3.0 / USB 3.1 Gen 1) and USB 3.2 Gen 2 (formerly USB 3.1 / USB 3.1 Gen 2).

## Technical specifications

Manufacturer	ROLINE GREEN
Product group	Cable
Product type	USB 3.2 Cable

Colour	black
Length	1 m
Scope of delivery	Cable without plastic bag, only marked with a paper label
Transfer quality	USB 3.2 Gen 2 SuperSpeed 10 Gbit/s (USB 3.1 Gen 2, USB 3.1)
Connection ports	USB Type C (USB-C) Male / USB Type C (USB-C) Male
Side 1 Connector Type	USB Type C (USB-C)
Side 1 Connector Gender	Male
Side 2 Connector Type	USB Type C (USB-C)
Side 2 Connector Gender	Male
Colour (Cable)	black
Max. resolution	3840 x 2160 @60Hz (4K, UHD-1)
Maximum data transfer rate	10 Gbit/s
Area of application	External
Supported charging technology	USB-PD - USB Power Delivery
Power (max.)	100 W
Cable shielding	Screened
Hand locking screws	no
Material (external cable mantle)	TPE
Cable LSOH	halogen-free
Weight	44.4 g
Height of packaging (single piece)	10 mm
Width of packaging (single piece)	100 mm
Depth of packaging (single piece)	100 mm

---

Package weight (single piece) 0.005 kg