



NOTE:

1. Electrical test:
 - (1). 100% open short & miss wire test;
 - (2). Insulation resistance: DC 300V 10M Ω ;
 - (3). Contactor resistance: 3Ω Max;
 - (4). Dielectric strength: 100V AC/Minute, 1mA.
2. RoHS and Reach Compliant
3. PRINTING: USB 2.0 CABLE, 28AWG×1P+28AWG×2C RECYCLED
4. The proportion for the recycled material is more than 50%.

MATERIAL LIST:

④	OUTER MOLD	RECYCLED PVC COLOR: BLACK	2	
③	USB B TYPE	USB B /M TYPE, THE PIN GOLD PLATING , THE SHELL FOR NICKEL PLATING	1	
②	USB A TYPE	USB A /M TYPE, THE PIN GOLD PLATING , THE SHELL FOR NICKEL PLATING	1	
①	CABLE	USB 2.0 28AWG (BC*1P)+28AWG (BC*2C)+AB AL-MG JACKET: RECYCLED PVC/black OD: 4.5±0.2mm	1	
NO.	PARTS NAME	SPECIFICATION STANDARD	QT' Y	REMARK

11.45.8818	USB2.0 Cable, A - B, M/M, 1.8m	1800±30
11.45.8808	USB2.0 Cable, A - B, M/M, 0.8m	800±20
ITEM NO.	DESC.	LENGTH(mm)

NEW		2023/12/19	A
BY	CHK	REVISION RECORD MODIFICATIONS	DATE
			REV.

