


Note:

ROHS 2.0 & REACH Compliant

2. The out jacket is conform to IEC60332-1, EN60754-2, EN 61034-2

3. Min. Bending Radius: Static: 30mm, Dynamic: 60mm

Test:

Grade Designation: Each to Reference

MATERIAL LIST:

⑫	LC Dust Cap White	2pcs	
⑪	LC/APC SM Ceramic Ferrule	2pcs	
⑩	LC Green Duplex Clip	1pcs	
⑨	LC Duplex Connector Green	2pcs	
⑧	LC 3.0 Boot White	2pcs	
⑦	LSH 3.0 Boot Green	2pcs	
⑥	Fiber Optical Cable Yellow OS2 G657.A2 9/125um Duplex Ø3.0*6.0mm LSZH	L	
⑤	Black Heat Shrink Tube	2pcs	
④	Ring 1、2	4pcs	
③	LSH 3.0 Boot Green	2pcs	
②	LSH Connector Green	2pcs	
①	LSH Metal Dust Cap	2pcs	
NO.	SPECIFICATION STANDARD	QT'Y	REMARK

Type	Single-Mode
Insertion Loss	≤0.2dB
Return Loss	≥60dB
Test Wavelength	1310nm
ITEM NO.	DESC.
21.15.9480	ROLINE FO Jumper Cable LSH-LC, APC, Duplex, 9/125um, OS2, 0.5m
21.15.9481	ROLINE FO Jumper Cable LSH-LC, APC, Duplex, 9/125um, OS2, 1m
21.15.9482	ROLINE FO Jumper Cable LSH-LC, APC, Duplex, 9/125um, OS2, 2m
21.15.9483	ROLINE FO Jumper Cable LSH-LC, APC, Duplex, 9/125um, OS2, 3m
21.15.9485	ROLINE FO Jumper Cable LSH-LC, APC, Duplex, 9/125um, OS2, 5m
21.15.9486	ROLINE FO Jumper Cable LSH-LC, APC, Duplex, 9/125um, OS2, 7.5m
21.15.9487	ROLINE FO Jumper Cable LSH-LC, APC, Duplex, 9/125um, OS2, 10m

		Add Min. Bending Radius	2022-1-24	A1
		NEW	2018-05-07	A
BY	CHK	REVISION RECORD MODIFICATIONS	DATE	REV.

SECOMP