

RXEF017S Product Details

Share

Print

Email

RXEF017S
(RF2666-000)
TE Internal Number: RF2666-000
 Active

PolySwitch Resettable Devices

Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Radial Application
- Vmax Interrupt = 60 V rms
- Imax Interrupt = 40 A
- Family Name = RXEF
- Radial Construction

[View all Features](#)

Quick Links

- Pricing & Availability
- Search for Tooling
- Product Feature Selector
- Contact Us About This Product

[Add to My Part List](#)

[Request Sample](#)

[Find Similar Products](#)

[Buy Product](#)

Documentation & Additional Information	
Product Drawings: - None Available Catalog Pages/Data Sheets: - None Available Product Specifications: RXEF017S (PDF, English) Application Specifications: - None Available Instruction Sheets: - None Available CAD Files: - None Available	Related Products: Tooling List all Documents

Product Features (Please use the Product Drawing for all design activity)	
Product Type Features: - Family Name = RXEF - CSA File Number = A78165 Electrical Characteristics: - Vmax Interrupt (V rms) = 60 - Imax Interrupt (A) = 40 - IH (Room Temperature) (A) = 0.17 - IT (Room Temperature) (A) = 0.34 - Rmin (Ω) = 3.30 - Rmax (Ω) = 5.210 - R1 Max [Post Trip] (Ω) = 8.00 - Power Dissipation (Typical) (W) = 0.48 - Power Dissipation (Max) (W) = 0.67 Termination Features: - Construction = Radial Body Features: - Lead Type = Straight Lead	Configuration Features: - Coating = Coated Industry Standards: RoHS/ELV Compliance = RoHS compliant, ELV compliant Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260°C - RoHS/ELV Compliance History = Always was RoHS compliant - UL File Number = E74889 - TUV Certificate No. = Available on request (per IEC 60730-1) Environmental: Operating Temperature (Max.) (°C) = 85 Operation/Application: - Application = Radial Packaging Features: - Packaging Method = Loose Piece Other: - Brand = Raychem

