

Miniature Fuse, 5 x 20 mm, Quick-Acting F, H, 250 VAC



## IEC 60127-2 · 250 VAC · Quick-Acting F

See below:

### Approvals and Compliances

#### Description

- IEC Standard Fuse
- H = High Breaking Capacity (Ceramic Tube)

#### Applications

- Primary Protection in Equipment

#### References

Pigtail Type [SP 5x20 Pigtail](#)  
Corresponding Fuseholder [FIZ](#); [FUA](#); [FUL](#); [FUP](#); [OGN](#)  
Assembled Fuseholder  
Fuse Kit [Fuse Kit FST 5x20 / SP 5x20](#); [Fuse Kit SP 5x20 / SPT 5x20](#)

#### Weblinks

[pdf data sheet](#), [html datasheet](#), [General Product Information](#), [Distributor-Stock-Check](#), [Detailed request for product](#)

#### Technical Data

|                          |                                                                                                                                                                            |
|--------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Rated Voltage            | 250 VAC                                                                                                                                                                    |
| Rated current            | 0.5 - 16 A                                                                                                                                                                 |
| Breaking Capacity        | 500 A - 1500 A                                                                                                                                                             |
| Characteristic           | Quick-Acting F                                                                                                                                                             |
| Admissible Ambient Temp. | -55 °C to 125 °C                                                                                                                                                           |
| Climatic Category        | 55/125/21 acc. to IEC 60068-1                                                                                                                                              |
| Material: Tube           | Ceramics                                                                                                                                                                   |
| Material: Endcaps        | Copper alloy, nickel-plated                                                                                                                                                |
| Unit Weight              | 1.18 g                                                                                                                                                                     |
| Storage Conditions       | 0 °C to 60 °C, max. 70% r.h.                                                                                                                                               |
| Product Marking          |  , Rated current, Rated Voltage, Characteristic, Breaking Capacity, Certification marks |

### Approvals and Compliances

Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in [Details about Approvals](#)

SCHURTER products are designed for use in industrial environments. They have approvals from independent testing bodies according to national and international standards. Products with specific characteristics and requirements such as required in the automotive sector according to IATF 16949, medical technology according to ISO 13485 or in the aerospace industry can be offered exclusively with customer-specific, individual agreements by SCHURTER.

#### Approvals

The approval mark is used by the testing authorities to certify compliance with the safety requirements placed on electronic products.

Approval Reference Type: SP 5x20

| Approval Logo                                                                       | Certificates                   | Certification Body | Description                                                     |
|-------------------------------------------------------------------------------------|--------------------------------|--------------------|-----------------------------------------------------------------|
|  | <a href="#">VDE Approvals</a>  | VDE                | VDE Certificate Number: 40009397                                |
|  | <a href="#">UL Approvals</a>   | UL                 | UR File Number: E41599                                          |
|  | <a href="#">CCC Approvals</a>  | CCC                | CCC Certificate Number: 2020970207000117 & more                 |
|  | <a href="#">KTL Approvals</a>  | KTL                | Korea Testing Laboratory                                        |
|  | <a href="#">METI Approvals</a> | METI               | Japan Electrical Safety and Environment technology Laboratories |

## Product standards

Product standards that are referenced

| Organization                                                                     | Design                | Standard           | Description                                     |
|----------------------------------------------------------------------------------|-----------------------|--------------------|-------------------------------------------------|
|  | Designed according to | IEC 60127-2/1      | Miniature fuses. Part 2. Cartridge fuse links   |
|  | Designed according to | UL 248-14          | Low voltage fuses - Part 14: Supplemental fuses |
|  | Designed according to | CSA22.2 No. 248.14 | Low-Voltage Fuses - Part 14: Supplemental Fuses |

## Application standards

Application standards where the product can be used

| Organization                                                                     | Design                         | Standard       | Description                                                                                   |
|----------------------------------------------------------------------------------|--------------------------------|----------------|-----------------------------------------------------------------------------------------------|
|  | Suitable for applications acc. | IEC/UL 62368-1 | Audio/video, information and communication technology equipment - Part 1: Safety requirements |


## Compliances

The product complies with following Guide Lines

| Identification                                                                     | Details                                        | Initiator   | Description                                                                                                                                                                                           |
|------------------------------------------------------------------------------------|------------------------------------------------|-------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|    | <a href="#">CE declaration of conformity</a>   | SCHURTER AG | The CE marking declares that the product complies with the applicable requirements laid down in the harmonisation of Community legislation on its affixing in accordance with EU Regulation 765/2008. |
|    | <a href="#">UKCA declaration of conformity</a> | SCHURTER AG | The UKCA marking declares that the product complies with the applicable requirements laid down in the British Amendment of Regulation (EC) 765/2008.                                                  |
|    | RoHS                                           | SCHURTER AG | Directive RoHS 2011/65/EU, Amendment (EU) 2015/863                                                                                                                                                    |
|   | China RoHS                                     | SCHURTER AG | The law SJ / T 11363-2006 (China RoHS) has been in force since 1 March 2007. It is similar to the EU directive RoHS.                                                                                  |
|  | REACH                                          | SCHURTER AG | On 1 June 2007, Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorization and Restriction of Chemicals 1 (abbreviated as "REACH") entered into force.                               |

## Dimension [mm]


 20 mm



## Pre-Arcing Time

| Rated Current In | 1.5 x In min. | 2.1 x In max. | 2.75 x In min. | 2.75 x In max. | 4.0 x In min. | 4.0 x In max. | 10.0 x In max. |
|------------------|---------------|---------------|----------------|----------------|---------------|---------------|----------------|
| 0.5 A - 4 A      | 60 min        | 30 min        | 10 ms          | 2 s            | 3 ms          | 300 ms        | 20 ms          |
| 5 A - 6.3 A      | 60 min        | 30 min        | 10 ms          | 3 s            | 3 ms          | 300 ms        | 20 ms          |
| 8 A - 10 A       | 30 min        | 30 min        | 40 ms          | 20 s           | 10 ms         | 1 s           | 30 ms          |
| 12.5 A - 16 A    | 15 min        | 30 min        | 40 ms          | 20 s           | 10 ms         | 1 s           | 30 ms          |

## Time-Current-Curves



## Variants

| Rated Current [A] | Rated Voltage [VAC] | Breaking Capacity | Voltage Drop 1.0 I <sub>n</sub> max. [mV] | Voltage Drop 1.0 I <sub>n</sub> typ. [mV] | Power Dissipation 1.5 I <sub>n</sub> max. [mW] | Power Dissipation 1.5 I <sub>n</sub> typ. [mW] | Melting I <sup>2</sup> t 10.0 I <sub>n</sub> typ. [A <sup>2</sup> s] |  |  |  |  |  | Order Number |
|-------------------|---------------------|-------------------|-------------------------------------------|-------------------------------------------|------------------------------------------------|------------------------------------------------|----------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|--------------|
| 0.5               | 250                 | 1)                | 1800                                      | 830                                       | 2500                                           | 2400                                           | 0.098                                                                | ●                                                                                     | ●                                                                                     | ●                                                                                     | ●                                                                                     | ●                                                                                     | 0001.1001    |
| 0.63              | 250                 | 1)                | 1500                                      | 800                                       | 2500                                           | 2400                                           | 0.207                                                                | ●                                                                                     | ●                                                                                     | ●                                                                                     | ●                                                                                     | ●                                                                                     | 0001.1002    |
| 0.8               | 250                 | 1)                | 1200                                      | 580                                       | 2500                                           | 2400                                           | 0.469                                                                | ●                                                                                     | ●                                                                                     | ●                                                                                     | ●                                                                                     | ●                                                                                     | 0001.1003    |
| 1                 | 250                 | 1)                | 1000                                      | 600                                       | 2500                                           | 2500                                           | 0.75                                                                 | ●                                                                                     | ●                                                                                     | ●                                                                                     | ●                                                                                     | ●                                                                                     | 0001.1004    |
| 1.25              | 250                 | 1)                | 800                                       | 270                                       | 4000                                           | 1000                                           | 0.538                                                                | ●                                                                                     | ●                                                                                     | ●                                                                                     | ●                                                                                     | ●                                                                                     | 0001.1005    |
| 1.6               | 250                 | 1)                | 600                                       | 350                                       | 4000                                           | 1600                                           | 0.755                                                                | ●                                                                                     | ●                                                                                     | ●                                                                                     | ●                                                                                     | ●                                                                                     | 0001.1006    |
| 2                 | 250                 | 1)                | 500                                       | 260                                       | 4000                                           | 1600                                           | 2                                                                    | ●                                                                                     | ●                                                                                     | ●                                                                                     | ●                                                                                     | ●                                                                                     | 0001.1007    |
| 2.5               | 250                 | 1)                | 400                                       | 260                                       | 4000                                           | 1900                                           | 3.28                                                                 | ●                                                                                     | ●                                                                                     | ●                                                                                     | ●                                                                                     | ●                                                                                     | 0001.1008    |
| 3.15              | 250                 | 1)                | 350                                       | 210                                       | 4000                                           | 1900                                           | 6.78                                                                 | ●                                                                                     | ●                                                                                     | ●                                                                                     | ●                                                                                     | ●                                                                                     | 0001.1009    |
| 4                 | 250                 | 1)                | 300                                       | 200                                       | 4000                                           | 2400                                           | 12.6                                                                 | ●                                                                                     | ●                                                                                     | ●                                                                                     | ●                                                                                     | ●                                                                                     | 0001.1010    |
| 5                 | 250                 | 1)                | 250                                       | 160                                       | 4000                                           | 2400                                           | 30.8                                                                 | ●                                                                                     | ●                                                                                     | ●                                                                                     | ●                                                                                     | ●                                                                                     | 0001.1011    |
| 6.3               | 250                 | 1)                | 200                                       | 150                                       | 4000                                           | 3200                                           | 36.7                                                                 | ●                                                                                     | ●                                                                                     | ●                                                                                     | ●                                                                                     | ●                                                                                     | 0001.1012    |
| 8                 | 250                 | 1)                | 200                                       | 140                                       | 4000                                           | 3900                                           | 81.9                                                                 | ●                                                                                     | ●                                                                                     | ●                                                                                     | ●                                                                                     | ●                                                                                     | 0001.1013    |
| 10                | 250                 | 1)                | 200                                       | 130                                       | 4000                                           | 3000                                           | 141                                                                  | ●                                                                                     | ●                                                                                     | ●                                                                                     | ●                                                                                     | ●                                                                                     | 0001.1014    |
| 12.5              | 250                 | 2)                | -                                         | 110                                       | -                                              | 6900                                           | 203                                                                  | ●                                                                                     | ●                                                                                     |                                                                                       |                                                                                       |                                                                                       | 0001.1015    |
| 16                | 250                 | 2)                | -                                         | 120                                       | -                                              | 7400                                           | 461                                                                  | ●                                                                                     |                                                                                       |                                                                                       |                                                                                       |                                                                                       | 0001.1016    |

Availability for all products can be searched real-time: <https://www.schurter.com/en/info-center/support-tools/stock-check-distributors>

1) IEC: H = 1500 A @ 250 VAC, p.f. = 0.7 - 0.8

1) UL: 10 kA @ 125 VAC, p.f. = 0.7 - 0.8 / 1500 A @ 250 VAC, p.f. = 0.7 - 0.8

2) IEC: 1000 A @ 250 VAC

2) UL: 500 A @ 125 VAC, p.f. = 0.7 - 0.8 / 1000 A @ 125 VAC / 500 A @ 250 VAC

## Packaging Unit

xxxx.xxxx  
xxxx.xxxx.G

Small Box Pack (10 pcs.)  
Bulk 128 x 91 x 60 mm (1000 pcs.)