

Fuse DTII 500V



See below:
[Approvals and Compliances](#)

Description

- Operation full range cable defensive fuses
- Over-load and short-circuit protection
- Colored characteristic detector in the middle
- Characteristic gG
- According to IEC 269

Technical Data

Rated Current In	2- 25A
Rated Voltage	500 VAC
Breaking Capacity	50kA
Rated Power Operating Frequency fe	50Hz

Basic Design

Insulator	Ceramic
Metal components	Brass

Approvals and Compliances

Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in [Details about Approvals](#)


Compliances

The product complies with following Guide Lines

Identification	Details	Initiator	Description
REACH	REACH	SCHURTER AG	On 1 June 2007, Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorization and Restriction of Chemicals 1 (abbreviated as "REACH") entered into force.

Time-Current-Curves

DT II - DT III



Variants

Rated current	Color	Packaging unit	Order Number	E-No.
[A]		Pcs		
2	rosé	25	0001.2021	800250209
4	brown	25	0001.2022	800250409
6	green	25	0001.2023	800250609
10	red	25	0001.2024	800251009
16	grey	25	0001.2025	800251509
20	blue	25	0001.2026	800252009
25	yellow	25	0001.2027	800252509

Availability for all products can be searched real-time: <https://www.schurter.com/en/info-center/support-tools/stock-check-distributors>