

CB-1026D-30 Product Details



CB-1026D-30
(1-1393136-8)

TE Internal Number: 1-1393136-8

 [Active](#)

Time Delay Relays

[Not EU RoHS or ELV Compliant](#)

Product Highlights:

- CB Series
- Input Voltage = 24 VDC
- Contact Arrangement = 2 Form C, DPDT, 2 C/O
- Contact Rating = 10A @ 30 VDC or 277 VAC
- Mounting Options = Socket

[View all Features](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

 [Add to My Part List](#)  [Request Sample](#)  [Find Similar Products](#)  [Buy Product](#)

Documentation & Additional Information

Product Drawings:

- None Available

Catalog Pages/Data Sheets:

- [CB CMOS IC Time Delay Relay](#) (PDF, English)

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files:

- None Available

Additional Information:

- [Product Line Information](#)

Additional Product Images:

- [Schematic](#)
- [Wiring Diagram](#)

Related Products:

- [Tooling](#)

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Termination Type = 8-Pin Octal Style Plug

Electrical Characteristics:

- Input Voltage (VDC) = 24
- Contact Rating = 10A @ 30 VDC or 277 VAC

Body Related Features:

- [Series](#) = CB

Contact Related Features:

- Mounting Options = Socket
- Mode of Operation = Delay on Operate
- Delay Time = 0.1 seconds to 1 second
- Type of Control = Knob
- Repeatability, Max. = $\pm$ 2%
- Approved Standards = CSA Certified, UL Recognized
- Contact Base Material = Silver Cadmium Oxide
- Approx. Dimensions (L x W x H) (mm [in]) = 61.10 x 45.20 x 74.60 [2.407 x 1.780 x 2.939]
- Enclosure = White Plastic Case

Configuration Related Features:

- [Contact Arrangement](#) = 2 Form C, DPDT, 2 C/O
- Multiple Timing Ranges = Without

Industry Standards:

- [RoHS/ELV Compliance](#) = Not ELV/RoHS compliant
- [Lead Free Solder Processes](#) = Not relevant for lead free process

Conditions for Usage:

- Temperature Range (?C) = -10 - +55

Other:

- Brand = Potter & Brumfield

Corporate Information

[Who We Are](#)

[Investors](#)

[News Room](#)

[Supplier Portal](#)

[Careers](#)

Quick Links

[Check Distributor Inventory](#)

[Cross Reference](#)

[Find Documents & Drawings](#)

[Product Compliance Support Center](#)

[Site Map](#)

Customer Support

[Email or Chat with Us](#)

[Find a Phone Number](#)

[Search Knowledge Base](#)

[Manage Your Account](#)