

## VTM3ECD Product Details



### VTM3ECD

(9-1437481-0)

TE Internal Number: 9-1437481-0

[Active](#)

### Time Delay Relays

[Not EU RoHS or ELV Compliant](#)

#### Product Highlights:

- VTM3 Interval Timing Module Series
- Input Voltage = 24 VAC
- Input Voltage = 24 VDC
- Contact Arrangement = 1 Form A, SPST-NO, 1 N/O Solid State
- Contact Rating = 1A

[View all Features](#)

### Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

[Add to My Part List](#) [Request Sample](#) [Find Similar Products](#) [Buy Product](#)

### Documentation & Additional Information

#### Product Drawings:

- None Available

#### Catalog Pages/Data Sheets:

- None Available

#### Product Specifications:

- None Available

#### Application Specifications:

- None Available

#### Instruction Sheets:

- None Available

#### CAD Files:

- None Available

#### Additional Information:

- [Product Line Information](#)

#### Additional Product Images:

- [Dimensional Drawing](#)

#### Related Products:

- [Tooling](#)

### Product Features (Please use the Product Drawing for all design activity)

#### Product Type Features:

- Termination Type = .250 x .032 Quick Connect Terminals

#### Electrical Characteristics:

- Input Voltage (VAC) = 24
- Input Voltage (VDC) = 24
- Contact Rating = 1A

#### Body Related Features:

- [Series](#) = VTM3 Interval Timing Module

#### Contact Related Features:

- Mounting Options = Mounting Holes
- Mode of Operation = Interval
- Delay Time = 0.5 seconds to 10 seconds
- Type of Control = External Resister
- Repeatability, Max. = +1%
- Approved Standards = CSA Certified, UL Recognized
- Approx. Dimensions (L x W x H) (mm [in]) = 50.80 x 50.80 x 22.48 [2.001 x 2.001 x .885]

#### Configuration Related Features:

- [Contact Arrangement](#) = 1 Form A, SPST-NO, 1 N/O Solid State
- Multiple Timing Ranges = Without

#### Industry Standards:

- [RoHS/ELV Compliance](#) = Not ELV/RoHS compliant
- [Lead Free Solder Processes](#) = Not suitable for lead free processing

#### Conditions for Usage:

- Temperature Range (?C) = -40 - +65

#### Other:

- Brand = Agastat

### Corporate Information

- [Who We Are](#)
- [Investors](#)
- [News Room](#)
- [Supplier Portal](#)
- [Careers](#)

### Quick Links

- [Check Distributor Inventory](#)
- [Cross Reference](#)
- [Find Documents & Drawings](#)
- [Product Compliance Support Center](#)
- [Site Map](#)

### Customer Support

- [Email or Chat with Us](#)
- [Find a Phone Number](#)
- [Search Knowledge Base](#)
- [Manage Your Account](#)