

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [1713151107](#)
Status: **Active**
Overview: Impel and Impel Plus Backplane Solutions
Description: Impel 90 Ohm, 4 Pair Vertical Backplane Header, 1.90mm Pitch, Unguided, Open Endwalls, 10 Columns, 80 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.36mm

Documents:

| | |
|---|---|
| Drawing (PDF) | Application Specification AS-171320-992-001 (PDF) |
| Product Specification PS-171320-999-001 (PDF) | Packaging Specification PK-78888-084-001 (PDF) |
| Application Specification AS-171320-990-001 (PDF) | Symbol Footprint Data SYM-171315-1107 (PDF) |
| Application Specification AS-171320-991-001 (PDF) | RoHS Certificate of Compliance (PDF) |

Agency Certification

UL E29179

General

| | |
|-------------------------------|--|
| Product Family | Backplane Connectors |
| Series | 171315 |
| Application | Backplane |
| Application Tooling Documents | TM-622018899 |
| Component Type | PCB Header |
| Overview | Impel and Impel Plus Backplane Solutions |
| Product Name | Impel |
| UPC | 889056650861 |

Physical

| | |
|--------------------------------|--------------------------------|
| Circuits (Loaded) | 80 |
| Circuits (maximum) | 80 |
| Color - Resin | Black |
| Durability (mating cycles max) | 200 |
| First Mate / Last Break | No |
| Guide to Mating Part | No |
| Keying to Mating Part | None |
| Material - Metal | High Performance Alloy (HPA) |
| Material - Plating Mating | Gold |
| Material - Plating Termination | Tin |
| Material - Resin | High Temperature Thermoplastic |
| Net Weight | 5.764/g |
| Number of Columns | 10 |
| Number of Pairs | 4 |
| Number of Rows | 8 |
| Orientation | Vertical |
| PC Tail Length | 1.30mm |
| PCB Locator | No |
| PCB Retention | None |
| PCB Thickness - Recommended | 1.00mm |
| Packaging Type | Tray |
| Pitch - Mating Interface | 1.90mm |
| Pitch - Termination Interface | 1.90mm |
| Plating min - Mating | 0.762µm |
| Temperature Range - Operating | -55° to +85°C |

Electrical

| | |
|-------------------------------|-----------|
| Current - Maximum per Contact | 0.75A |
| Data Rate | 40.0 Gbps |
| Impedance | 90Ω |



Series image - Reference only

EU ELV

Not Relevant

EU RoHS

Compliant

REACH SVHC

Not Contained Per -
D(2020)4578-DC (25
June 2020)

Halogen-Free

Status

Low-Halogen

For more information, please visit [Contact US](#)

China ROHS

ELV

RoHS Phthalates

China RoHS

Green Image

Not Relevant

Not Contained

Search Parts in this Series

[171315 Series](#)

Mates With

[Impel Right-Angle Daughtercard
1713201020](#)

Application Tooling | FAQ

Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.

Global

Description

Product #

Impel Backplane [622018952](#)

Module Installation

Press-In Tool

Shield Type
Voltage - Maximum

Full Shield
150V AC (RMS)/DC

Material Info

Reference - Drawing Numbers

Application Specification

AS-171320-990-001, AS-171320-991-001,
AS-171320-992-001

Packaging Specification

PK-78888-084-001

Product Specification

PS-171320-999-001

Sales Drawing

SD-171315-0001-001

Symbol/Footprint Data

SYM-171315-1107

This document was generated on 07/21/2020

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION