

Features

- Connects a Sure Cross® Gateway, a MultiHop Radio, or an RS-485 sensor to a Windows PC USB port
- **BWA-HW-006** supplies power to one Gateway, one MultiHop Radio operating at 250 mW, or one RS-485 sensor
- **BWA-UCT-900** supplies power for one Gateway or one MultiHop Radio operating at 1 Watt
- Supports baud rates of 9600, 19200, and 38400
- Converts USB to RS-485 (2-wire) with a M12 connector
- Supports Windows XP and Vista
- Download the User Configuration Software, MultiHop Configuration Software, or Sensor Configuration Software free from Banner Engineering's Wireless I/O Products website
- Includes cordset **MQDMC-401** for use with the DX80...C models

BWA-UCT-900 and MQDMC-401



Do not use **BWA-HW-006** to connect a Performance Gateway or MultiHop Radio operating in 1-Watt mode. Always configure the Performance and MultiHop models to operate in 250 mW mode before connecting them to your computer to avoid damaging your USB port.

To supply power to 1 Watt radios during configuration, use cable **BWA-UCT-900**.

When plugging this cable into your computer for the first time, give the cable 1 to 2 minutes to check your computer for the proper driver, download the driver, then install it. Plug the cable into your Gateway; the cable should supply enough power to the Gateway to configure it.

For additional information, updated documentation, and a list of accessories, refer to Banner Engineering's website, www.bannerengineering.com.

Models


Model	Adapter	Length
BWA-HW-006	RS-485 to USB	1 meter
BWA-UCT-900	RS-485 to USB, with wall plug to power 1 Watt radios during configuration	

Both cordsets include cordset model **MQDMC-401** for use with the DX80...C models.

4-pin M12 Female Connection

Connecting power to the communication pins will cause permanent damage.

4-pin M12 female connector wiring

4-pin M12 Female Quick Disconnect	Pin	Wire Color	DX80 Wiring	DX80...C Wiring
	1	Brown	10 V DC to 30 V DC	V+
	2	White	RS-485 Tx +	Tx
	3	Blue	DC common (GND)	V-
	4	Black	RS-485 Rx -	Rx

Specifications

Input Power

BWA-HW-006: 5 V DC from USB port

BWA-UCT-900: 5 V DC from USB port; 100 to 240 V AC from the plug-in wall transformer

Output Power

BWA-HW-006: 10 V DC power output for a single device transmitting at 250 mW or less

BWA-UCT-900: 24 V DC power output for a single device transmitting at 1 Watt

Current Draw

Models BWA-HW-006/073/083: 60 mA

Operating Parameters

0 °C to +50 °C (+32 °F to +122 °F)

95% maximum relative humidity (non-condensing)

USB

Connector: USB type A plug

Standard: 2.0

RS-485

2-wire; 9.6k, 19.2k, or 38.4k; 8 data bits; 1 stop bit; no parity

Connector: M12 connector compatible with Banner Sure Cross Gateways and data radios

Banner Compatible Devices

DX80G*, DR9M, DR2M models

M12FTH3Q Temperature and Humidity Sensor; **M12FT3Q** Temperature Sensor; **GPS50M** GPS Sensor

BWA-HW-006 will not power a MultiHop radio in 1 Watt mode. Use **BWA-UCT-900** to supply power to 1 Watt radios. To use **BWA-HW-006** with a MultiHop radio, set the radio to operate at 250 mW.

Length

1 meter

Maintenance

Product label to be cleaned with dry or water-dampened cloth only

FCC Part 15 Class B for Unintentional Radiators

(Part 15.105(b)) This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

(Part 15.21) Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate this equipment.

Industry Canada ICES-003(B)

This device complies with CAN ICES-3 (B)/NMB-3(B). Operation is subject to the following two conditions: 1) This device may not cause harmful interference; and 2) This device must accept any interference received, including interference that may cause undesired operation.

Cet appareil est conforme à la norme NMB-3(B). Le fonctionnement est soumis aux deux conditions suivantes : (1) ce dispositif ne peut pas occasionner d'interférences, et (2) il doit tolérer toute interférence, y compris celles susceptibles de provoquer un fonctionnement non souhaité du dispositif.

Banner Engineering Corp Limited Warranty

Banner Engineering Corp. warrants its products to be free from defects in material and workmanship for one year following the date of shipment. Banner Engineering Corp. will repair or replace, free of charge, any product of its manufacture which, at the time it is returned to the factory, is found to have been defective during the warranty period. This warranty does not cover damage or liability for misuse, abuse, or the improper application or installation of the Banner product.

THIS LIMITED WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES WHETHER EXPRESS OR IMPLIED (INCLUDING, WITHOUT LIMITATION, ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE), AND WHETHER ARISING UNDER COURSE OF PERFORMANCE, COURSE OF DEALING OR TRADE USAGE.

This Warranty is exclusive and limited to repair or, at the discretion of Banner Engineering Corp., replacement. **IN NO EVENT SHALL BANNER ENGINEERING CORP. BE LIABLE TO BUYER OR ANY OTHER PERSON OR ENTITY FOR ANY EXTRA COSTS, EXPENSES, LOSSES, LOSS OF PROFITS, OR ANY INCIDENTAL, CONSEQUENTIAL OR SPECIAL DAMAGES RESULTING FROM ANY PRODUCT DEFECT OR FROM THE USE OR INABILITY TO USE THE PRODUCT, WHETHER ARISING IN CONTRACT OR WARRANTY, STATUTE, TORT, STRICT LIABILITY, NEGLIGENCE, OR OTHERWISE.**

Banner Engineering Corp. reserves the right to change, modify or improve the design of the product without assuming any obligations or liabilities relating to any product previously manufactured by Banner Engineering Corp. Any misuse, abuse, or improper application or installation of this product or use of the product for personal protection applications when the product is identified as not intended for such purposes will void the product warranty. Any modifications to this product without prior express approval by Banner Engineering Corp will void the product warranties. All specifications published in this document are subject to change; Banner reserves the right to modify product specifications or update documentation at any time. Specifications and product information in English supersede that which is provided in any other language. For the most recent version of any documentation, refer to: www.bannerengineering.com.

For patent information, see www.bannerengineering.com/patents.