

Features



Banner's TL70 Tower Light is a 70 mm, modular LED indicator with extremely bright and uniform light. The modularity gives the user flexibility to customize tower lights as needed and change positions in the field. The TL70 is also available preassembled for easy installation.

- 100 to 240 V AC operation
- Connection options include 1/2-20 quick disconnect and cabled versions
- Uses the same light and audible segments as the DC voltage powered TL70
- Light segments have user-selectable solid ON or flashing
- Up to six colors, or five colors plus audible, in one device
- Rugged, water-resistant IP65 housing with UV-stabilized material
- Bright, uniform indicator segments appear gray when off to eliminate false indications from ambient light

Models

TL70 Base - Model Key

Housing	Power	—	Connection ⁽¹⁾	Housing Color
B-TL70	Z	—	Q5	
Base segment	Z = AC		5 = 2 m (6.5 ft) unterminated 5-wire PVC-jacketed cable (1-4 modules) 7 = 2 m (6.5 ft) unterminated 7-wire PVC-jacketed cable (5-6 modules) Q5 = Integral 5-pin 1/2 in. 20UNF male quick-disconnect connector (1-4 modules)	Blank = Black C = Gray

TL70 Segments - Model Key

Housing	—	Color/Alarm	Housing Color
SG-TL70	—	R	
TL70 Segment		G = Green Y = Yellow R = Red B = Blue W = White O = Orange A = Standard Audible AL = Loud Audible ALM = Loud Multi-Tone Audible AP = Programmable Audible	Blank = Black C = Gray

Select the 5-pin/wire base for tower light configurations of up to 4 modules. Select the 7-wire base for tower light configurations of up to 6 modules.

- Example base model number: B-TL70Z-Q5
- Example light segment model number: SG-TL70-G
- Example audible segment model number: SG-TL70-A

TL70 Pre-Assembled Models - Model Key

Housing	Color/Position						Audible Alarm ⁽²⁾	Housing Color	Connection ⁽¹⁾
	1	2	3	4	5	6			
TL70Z	W	B	G	Y	R				Q

Continued on page 2

⁽¹⁾ Quick-disconnect connector models require a mating cordset.

⁽²⁾ Not available with six module lights.

Continued from page 1

Housing	Color/Position						Audible Alarm	Housing Color	Connection ⁽¹⁾
	1	2	3	4	5	6			
	Blank = None G = Green Y = Yellow R = Red B = Blue W = White O = Orange						Blank = None A = Standard Audible AL = Loud Audible AP = Programmable Audible	Blank = Black C = Gray	Blank = 2 m (6.5 ft) integral PVC-jacketed cable Q = Integral 5-pin 1/2 in. 20UNF male quick-disconnect connector ⁽³⁾

- Example pre-assembled model number: TL70ZGYRAQ.

Use a 5-pin cordset for 1 to 4 modules.

WARNING:



- **Risk of hearing loss**
- All effective warning horns produce loud sounds that could cause, in certain situations, permanent hearing loss.
- Install the device far enough away from potential listeners to limit their exposure while still maintaining its effectiveness. Reference OSHA Code of Federal Regulations 1910.95 Noise Standard for guidelines about permissible noise exposure levels.

For more information regarding other TL70 Audible models, refer to the following documents:


- TL70 Loud Multi-Tone Audible Tower Light Module datasheet (p/n [195189](#))
- TL70 Programmable Audible Tower Light Module datasheet (p/n [196627](#))

Configuring the Modules



Turn on the appropriate DIP switch to set the order of the components, counting up from the tower light's base.

⁽³⁾ Limited to four module lights.




Assembly Options		DIP Switches							
		1	2	3	4	5	6	7	8
Light and Standard Audible Components	Module 1	ON							
	Module 2		ON						
	Module 3			ON					
	Module 4				ON				
	Module 5					ON			
	Module 6						ON		
Light and Module Flash Rate	3 Hz							ON	OFF
	1.5 Hz							ON	ON
	Solid On*							OFF	OFF
Standard Audible Module Settings	Pulse 1.5 Hz							ON	OFF
	Chirp Alarm							ON	ON
	Siren Alarm							OFF	ON
	Continuous Alarm*							OFF	OFF

Assembly Options		DIP Switches									
		1	2	3	4	5	6	7	8	9	10
Loud Audible Module Settings	Pulse 1.5 Hz							ON	OFF		
	Chirp Alarm							ON	ON		
	Siren Alarm							OFF	ON		
	Continuous Alarm*							OFF	OFF		
	Low Intensity*									OFF	OFF
	Med. Intensity									ON	OFF
	Med./Loud Intensity									OFF	ON
	Loud Intensity									ON	ON

* Factory default setting

Assembling the Modules




To assemble the modules:

1. Align the notches on each module and press together.
2. Rotate the top module clockwise to lock into place (notches shown in the locked position).

NOTE: DIP switches should remain in the default off position.

Wiring



Specifications

Supply Voltage and Current

100 V AC to 240 V AC; 50 Hz to 60 Hz
Maximum current per color or audible module:
70 mA at 120 V AC and 60 Hz
50 mA at 230 V AC and 50 Hz

Supply Protection Circuitry

Protected against transient voltages

Leakage Current Immunity

500 μ A
Application Note: The use of relay output PLC is recommended since there is no leakage current. Solid state output PLCs often have leakage current above 1 mA and, therefore, turn the light on in the off state. To counteract the leakage current, a shunt resistor must be used. A resistor must be applied from the neutral wire of the device to the hot wire of each channel of the device.

Indicators

1 to 6 colors depending on model: Green, Red, Yellow, Blue, White, and Orange
Flash rates: 1.5 Hz $\pm$ 10% and 3 Hz $\pm$ 10%
LEDs are independently selected

Indicator Response Time

Off Response: 20 ms (maximum)
On Response: 240 ms (maximum)

Indicator Characteristics

Color	Dominant Wavelength (nm) or Color Temperature (CCT)	Color Coordinates ⁽⁴⁾		Lumen Output (Typical at 25 °C)
		x	y	
Green	525 nm	–	–	92
Red	625 nm	–	–	40
Yellow	590 nm	–	–	22
Blue	470 nm	–	–	32
White	5000 K	–	–	125
Orange	–	0.66	0.33	33

Audible Alarm

Standard Audible Alarm: 2.6 kHz $\pm$ 250 Hz oscillation frequency; maximum intensity (typical) 92 dB at 1 m (3.3 ft)
Loud Audible Alarm: 2.6 kHz $\pm$ 250 Hz oscillation frequency; maximum intensity (typical) at 1 m (3.3 ft) (see table)

DIP Switches		Max Intensity (Loud Audible)
9	10	
ON	ON	Intensity 4: 101 dB
OFF	ON	Intensity 3: 99 dB
ON	OFF	Intensity 2: 92 dB
OFF	OFF	Intensity 1: 85 dB

⁽⁴⁾ Refer to CIE 1931 chromaticity diagram or color chart, to show equivalent color with indicated color coordinates.

Audible Adjustment

Standard Audible Alarm: Mechanical adjustment: Rotate the cover until the desired volume is reached

Loud Audible Alarm: Electronic adjustment: Select the desired volume using DIP switches 9 and 10

Typical Reduction in Sound Intensity with Audible Adjustment (maximum to minimum):

- **Standard Audible:** 8 dB
- **Loud Audible:** 16 dB

Construction

Bases, segments, covers: polycarbonate

Connections

Integral 5-pin 1/2 in. 20UNF male quick-disconnect connector, 2 m (6.5 ft) unterminated 5-wire PVC-jacketed cable, or 2 m (6.5 ft) unterminated 7-wire PVC-jacketed cable, depending on model

Vibration and Mechanical Shock

Vibration: 10 Hz to 55 Hz, 0.5 mm peak-to-peak amplitude per IEC 60068-2-6

Shock: 15G 11 ms duration, half sine wave per IEC 60068-2-27

Operating Conditions

−40 °C to +50 °C (−40 °F to +122 °F)

95% at +50 °C maximum relative humidity (non-condensing)

Environmental Rating

IP65

Certifications

Banner Engineering BV
Park Lane, Culliganlaan 2F bus 3
1831 Diegem, BELGIUM



Dimensions

All measurements are listed in millimeters [inches], unless noted otherwise. The measurements provided are subject to change.

Image	Model	Height (H)
	1 light module	155.6 mm (6.13 in)
	1 light module, 1 audible module	212.3 mm (8.36 in)
	2 light modules	205.3 mm (8.08 in)
	2 light modules, 1 audible module	262 mm (10.31 in)
	3 light modules	255 mm (10.04 in)
	3 light modules, 1 audible module	311.7 mm (12.27 in)
	4 light modules	304.7 mm (12 in)
	4 light modules, 1 audible module	361.4 mm (14.23 in)
	5 light modules	354.4 mm (13.95 in)
	5 light modules, 1 audible module	411.1 mm (16.19 in)
	6 light modules	404.1 mm (15.91 in)

Accessories

Cordsets

All measurements are listed in millimeters, unless noted otherwise. The measurements provided are subject to change.

5-Pin Single-Ended 1/2-In Dual Key Female Cordsets				
Model	Length	Style	Dimensions	Pinout (Female)
MQAC2-506	2 m (6.56 ft)	Straight		
MQAC2-515	5 m (16.4 ft)			
MQAC2-530	9.14 m (30 ft)			

Mounting Brackets


All measurements are listed in millimeters, unless noted otherwise. The measurements provided are subject to change.

SMB30A

- Right-angle bracket with curved slot for versatile orientation
- Clearance for M6 (¼ in) hardware
- Mounting hole for 30 mm sensor
- 12-gauge stainless steel

Hole center spacing: A to B=40

Hole size: A=ø 6.3, B= 27.1 × 6.3, C=ø 30.5




SMB30MM

- 12-gauge stainless steel bracket with curved mounting slots for versatile orientation
- Clearance for M6 (¼ in) hardware
- Mounting hole for 30 mm sensor

Hole center spacing: A = 51, A to B = 25.4

Hole size: A = 42.6 × 7, B = ø 6.4, C = ø 30.1




SMBAMS30P

- Flat SMBAMS series bracket
- 30 mm hole for mounting sensors
- Articulation slots for 90°+ rotation
- 12-gauge 300 series stainless steel

Hole center spacing: A=26.0, A to B=13.0


Hole size: A=26.8 × 7.0, B=ø 6.5, C=ø 31.0



SSA-MBK-EEC1

- Single 30 mm hole
- 8 gauge steel, black finish (powder coat)
- Front surface for customer-applied labels


Hole size: A = ø 7, B = ø 30



LMBE12RA35

- Direct mounting of stand-off pipe, with common bracket type
- Zinc-plated steel
- 1/2-14 NPSM nut
- Mounting distance from the wall to the center of the 1/2-14 NPSM nut is 35 mm


Hole center spacing: 20.0



LMBE12RA45

- Direct mounting of stand-off pipe, with common bracket type
- Zinc-plated steel
- 1/2-14 NPSM nut
- Mounting distance from the wall to the center of the 1/2-14 NPSM nut is 45 mm



Hole center spacing: 35.0




Elevated Mount System

Model			Description	Components
SA-M30 - Black Polycarbonate			- Streamlined black PC or Gray PC thread cover - Covers the outer M30 threads on the light's base - Mounting hardware included	
SA-M30C - Gray Polycarbonate				
Polished 304 Stainless Steel	Black Anodized Aluminum	Clear Anodized Aluminum	- Elevated-use stand-off pipe (½ in. NPSM/DN15) - Polished 304 stainless steel, black anodized aluminum, or clear anodized aluminum surface ½ in. NPT thread at both ends: one end screws into the internal threads of the light's base, and one end screws into the mounting base adapter/cover - Compatible with most industrial environments	
SOP-E12-150SS 150 mm (6 in) long	SOP-E12-150A 150 mm (6 in) long	SOP-E12-150AC 150 mm (6 in) long		
SOP-E12-300SS 300 mm (12 in) long	SOP-E12-300A 300 mm (12 in) long	SOP-E12-300AC 300 mm (12 in) long		
SOP-E12-900SS 900 mm (36 in) long	SOP-E12-900A 900 mm (36 in) long	SOP-E12-900AC 900 mm (36 in) long		
SA-E12M30 - Black Acetal				
SA-E12M30C - White UHMW			- Streamlined black acetal or white UHMW mounting base adapter/cover - Connects between ½ in. NPSM/DN15 pipe and 30 mm (1-3/16 in) drilled hole - Mounting hardware included	

Pipe Mounting Flange

Model	Description	Construction	
SA-F12	- Elevated-use stand-off pipes (½ in. NPSM/DN15) - M5 mounting hardware and nitrile gasket included	Die-cast zinc base with black paint	
SA-F12-3	- Elevated-use stand-off pipes (½ in. NPSM/DN15) - M4 mounting hardware and nitrile blend gasket included	Black Polycarbonate	

Foldable Mounting Brackets

Model	Description	Construction	
SA-FFB12	- For use with 1/2 inch stand-off pipes - Stainless steel hardware	Black polycarbonate	
SA-FFB12C		Gray polycarbonate	

LMB Sealed Right-Angle Bracket

Model	Description	
LMB30RA - Black polycarbonate LMB30RAC - Gray polycarbonate	Direct-Mount Models - Bracket kit with base, 30 mm adapter, set screw, fasteners, O-rings, and gaskets.	

Continued on page 8

Continued from page 7

Model	Description	
LMBE12RA - Black polycarbonate LMBE12RAC - Gray polycarbonate	• Pipe-Mount Models • Bracket kit with base, ½-14 pipe adapter, set screw, fasteners, O-rings, and gaskets • For use with stand-off pipe (listed and sold separately)	

Banner Engineering Corp Limited Warranty

Banner Engineering Corp. warrants its products to be free from defects in material and workmanship for one year following the date of shipment. Banner Engineering Corp. will repair or replace, free of charge, any product of its manufacture which, at the time it is returned to the factory, is found to have been defective during the warranty period. This warranty does not cover damage or liability for misuse, abuse, or the improper application or installation of the Banner product.

THIS LIMITED WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES WHETHER EXPRESS OR IMPLIED (INCLUDING, WITHOUT LIMITATION, ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE), AND WHETHER ARISING UNDER COURSE OF PERFORMANCE, COURSE OF DEALING OR TRADE USAGE.

This Warranty is exclusive and limited to repair or, at the discretion of Banner Engineering Corp., replacement. **IN NO EVENT SHALL BANNER ENGINEERING CORP. BE LIABLE TO BUYER OR ANY OTHER PERSON OR ENTITY FOR ANY EXTRA COSTS, EXPENSES, LOSSES, LOSS OF PROFITS, OR ANY INCIDENTAL, CONSEQUENTIAL OR SPECIAL DAMAGES RESULTING FROM ANY PRODUCT DEFECT OR FROM THE USE OR INABILITY TO USE THE PRODUCT, WHETHER ARISING IN CONTRACT OR WARRANTY, STATUTE, TORT, STRICT LIABILITY, NEGLIGENCE, OR OTHERWISE.**

Banner Engineering Corp. reserves the right to change, modify or improve the design of the product without assuming any obligations or liabilities relating to any product previously manufactured by Banner Engineering Corp. Any misuse, abuse, or improper application or installation of this product or use of the product for personal protection applications when the product is identified as not intended for such purposes will void the product warranty. Any modifications to this product without prior express approval by Banner Engineering Corp will void the product warranties. All specifications published in this document are subject to change; Banner reserves the right to modify product specifications or update documentation at any time. Specifications and product information in English supersede that which is provided in any other language. For the most recent version of any documentation, refer to: www.bannerengineering.com.

For patent information, see www.bannerengineering.com/patents.