



## | RPC SERIES

### PROPORTIONAL CONTROL SOLID STATE RELAYS



#### Features

- Proportional controller
- Ratings from 15A to 40A @ 480 VAC
- 500k or 1M Ohm potentiometer control
- KS100 Protective Cover Included
- For use with resistive loads only

#### PRODUCT SELECTION

| Description | 15 A    | 25 A    | 40 A    |
|-------------|---------|---------|---------|
| 120 Vrms    | RPC1215 | RPC1225 | RPC1240 |
| 240 Vrms    | RPC2415 | RPC2425 | RPC2440 |
| 480 Vrms    | RPC4815 | RPC4825 | RPC4840 |

#### OUTPUT SPECIFICATIONS (VOLTAGE) <sup>1</sup>

| Description                                                           | 120 VAC | 240 VAC | 480 VAC |
|-----------------------------------------------------------------------|---------|---------|---------|
| Operating Voltage (47-63 Hz) [Vrms]                                   | 90-130  | 200-240 | 400-480 |
| Transient Overvoltage [Vpk]                                           | 400     | 600     | 1200    |
| Maximum Off-State Leakage Current @ Rated Voltage [mArms]             | 10      | 7       | 3       |
| Minimum Off-State dv/dt @ Maximum Rated Voltage [V/μsec] <sup>2</sup> | 5000    | 500     | 500     |
| Snubber (Internal)                                                    | yes     | yes     | no      |

#### OUTPUT SPECIFICATIONS (CURRENT) <sup>1</sup>

| Description                                                         | 15 A | 25 A | 40 A |
|---------------------------------------------------------------------|------|------|------|
| Maximum Load Current [Arms] <sup>3</sup>                            | 15   | 25   | 40   |
| Minimum Load Current [mArms]                                        | 70   | 80   | 90   |
| Maximum Surge Current (16.6ms) [Apk]                                | 150  | 250  | 625  |
| Maximum On-State Voltage Drop @ Rated Current [Vpk]                 | 1.6  | 1.6  | 1.6  |
| Thermal Resistance Junction to Case (Rjc) [°C/W]                    | 1.48 | 1.02 | 0.63 |
| Maximum I <sup>2</sup> t for Fusing (8.3 msec) [A <sup>2</sup> sec] | 94   | 260  | 1620 |

● INPUT SPECIFICATIONS <sup>1</sup>


| Description                         | RPC12XX     | RPC24XX   | RPC48XX   |
|-------------------------------------|-------------|-----------|-----------|
| Variable Resistor Size <sup>4</sup> | 150K (1/2W) | 1M (1/2W) | 1M (1/2W) |

● GENERAL SPECIFICATIONS


| Description                                       |                                                                                           |
|---------------------------------------------------|-------------------------------------------------------------------------------------------|
| Minimum Power Factor (with Maximum Load)          | 0.6                                                                                       |
| Dielectric Strength, Input/Output/Base (50/60 Hz) | 2500 Vrms                                                                                 |
| Ambient Operating Temperature Range               | -30 to 80 °C                                                                              |
| Ambient Storage Temperature Range                 | -40 to 125 °C                                                                             |
| Weight (typical)                                  | 3.2 oz (90g)                                                                              |
| Encapsulation                                     | Thermally conductive Epoxy                                                                |
| Terminals                                         | Screws and saddle Clamps Furnished, Unmounted                                             |
| Recommended Terminal Screw Torque Range:          | 6-32 Screws -10 lb-in.<br>8-32 and 10-32 Screws -20 lb-in.<br>(Screws dry without grease) |

● MECHANICAL SPECIFICATIONS

\*Tolerances: ±0.02 in / 0.5 mm  
All dimensions are in: inches [millimeters]






## WIRING DIAGRAM






All terminals are  
at Line Voltage  
Potential.

Variable Resistance

## THERMAL DERATE INFORMATION



## PERCENTAGE ON VS INPUT RESISTANCE



## GENERAL NOTES

- (1) All parameters at 25°C unless otherwise specified.
- (2) Off-State dv/dt test method per EIA/NARM standard RS-443
- (3) Heat sinking required, see derating curves.
- (4) Potentiometer should be line voltage rated.

## AGENCY APPROVALS & CERTIFICATIONS



## WARNINGS



### RISK OF MATERIAL DAMAGE AND HOT ENCLOSURE

- The product's side panels may be hot, allow the product to cool before touching
- Follow proper mounting instructions including torque values
- Do not allow liquids or foreign objects to enter this product

**Failure to follow these instructions can result in serious injury, or equipment damage.**



### HAZARD OF ELECTRIC SHOCK, EXPLOSION OR ARC FLASH

- Disconnect all power before installing or working with this equipment
- Verify all connections and replace all covers before turning on power

**Failure to follow these instructions will result in death or serious injury.**

Sensata Technologies, Inc. ("Sensata") datasheets are solely intended to assist designers ("Buyers") who are developing systems that incorporate Sensata products (also referred to herein as "components"). Buyer understands and agrees that Buyer remains responsible for using its independent analysis, valuation, and judgment in designing Buyer's systems and products. Sensata datasheets have been created using standard laboratory conditions and engineering practices. Sensata has not conducted any testing other than that specifically described in the published documentation for a particular datasheet. Sensata may make corrections, enhancements, improvements, and other changes to its datasheets or components without notice.

Buyers are authorized to use Sensata datasheets with the Sensata component(s) identified in each particular datasheet. HOWEVER, NO OTHER LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OTHERWISE TO ANY OTHER SENSATA INTELLECTUAL PROPERTY RIGHT, AND NO LICENSE TO ANY THIRD PARTY TECHNOLOGY OR INTELLECTUAL PROPERTY RIGHT, IS GRANTED HEREIN. SENSATA DATASHEETS ARE PROVIDED "AS IS". SENSATA MAKES NO WARRANTIES OR REPRESENTATIONS WITH REGARD TO THE DATASHEETS OR USE OF THE DATASHEETS, EXPRESS, IMPLIED, OR STATUTORY, INCLUDING ACCURACY OR COMPLETENESS. SENSATA DISCLAIMS ANY WARRANTY OF TITLE AND ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, QUIET ENJOYMENT, QUIET POSSESSION, AND NON-INFRINGEMENT OF ANY THIRD PARTY INTELLECTUAL PROPERTY RIGHTS WITH REGARD TO SENSATA DATASHEETS OR USE THEREOF.

All products are sold subject to Sensata's terms and conditions of sale supplied at [www.sensata.com](http://www.sensata.com). SENSATA ASSUMES NO LIABILITY FOR APPLICATIONS ASSISTANCE OR THE DESIGN OF BUYERS' PRODUCTS. BUYER ACKNOWLEDGES AND AGREES THAT IT IS SOLELY RESPONSIBLE FOR COMPLIANCE WITH ALL LEGAL, REGULATORY, AND SAFETY-RELATED REQUIREMENTS CONCERNING ITS PRODUCTS, AND ANY USE OF SENSATA COMPONENTS IN ITS APPLICATIONS, NOTWITHSTANDING ANY APPLICATIONS-RELATED INFORMATION OR SUPPORT THAT MAY BE PROVIDED BY SENSATA.

Mailing Address: Sensata Technologies, Inc., 529 Pleasant Street, Attleboro, MA 02703, USA

## CONTACT US

### Americas

+1 (800) 350 2727  
[sales.crydom@sensata.com](mailto:sales.crydom@sensata.com)

### Europe, Middle East & Africa

+44 (1202) 416170  
[ssr-info.eu@sensata.com](mailto:ssr-info.eu@sensata.com)

### Asia Pacific

[sales.isasia@list.sensata.com](mailto:sales.isasia@list.sensata.com)  
China +86 (21) 2306 1500  
Japan +81 (45) 277 7117  
Korea +82 (31) 601 2004  
India +91 (80) 67920890  
Rest of Asia +886 (2) 27602006 ext 2808