


PKSEP6 SERIES

SMD Transformer for Ultrasonic Sensors



*RoHS COMPLIANT
& AEC-Q200 COMPLIANT

Features

- Ferrite core
- EP 6 SMD type
- Shielding for optimized EMC-behavior
- Five U-shape terminals
- AEC-Q200 compliant & automotive grade
- RoHS compliant*

Applications

- Ultrasonic sensors
- Ultrasonic park assist
- Industrial distance measuring
- Robotics

Sustainability

- Small size reduces material use
- Eco-logistics-friendly packing
- Recyclable ESD-safe packaging
- ISO 14001, low impact energy
- Responsibly sourced and produced
- Meets EU 94/62/EC standards

Product Overview

Bourns® PKSEP6 Series Impedance Matching Transformers are available with 0.23 ~ 5.0 mH inductance and various turns ratios, with extended values and customized values encouraged. This series also features frequency ranges between 50 kHz and 300 kHz and above and temperature ratings from -40°C to +90°C.

The PKSEP6 Series Impedance Matching Transformer platform enables ideal impedance matching between ultrasonic transducers and driver integrated circuits. Target applications include, but are not limited to, automotive parking assistance, industrial robots, drones, logistics robots, automated guided vehicles (AGVs), and fill level measurement systems.

Electrical Specifications (@ T_A = 25 °C Unless Otherwise Noted)

Bourns Part Number	Inductance (4-6) @ 52 kHz, 0.1 V	Rdc N1-1, N1-2	Rdc N2	Turns Ratio N1-1:N1-2:N2	Hi-Pot N1-1, N1-2 to N2	Weight
PKSEP6A09S	0.23 mH ±10 %	0.26 Ω Max.	7.2 Ω Max.	1:1:9 ±2 %	200 Vrms 50 Hz, 1 s No Breakdown	Approximately 1.15 g
PKSEP6A08S	3.0 mH ±10 %	0.72 Ω Max.	28.5 Ω Max.	1:1:8.42 ±2 %		
PKSEP6B08S	3.18 mH ±8 %	1.8 Ω Max.	37.5 Ω Max.	1:1:7.9 ±2 %		
PKSEP6A15S	4.2 mH ±10 %	0.62 Ω Max.	34.5 Ω Max.	1:1:15 ±2 %		
PKSEP6A10S	5.0 mH ±10 %	0.9 Ω Max.	36 Ω Max.	1:1:10.1 ±2 %		

Environmental Specifications

Operating Temperature -40 °C to +90 °C
(Temperature Rise Included)
Storage Temperature -25 °C to +85 °C
Moisture Sensitivity Level 1

Materials

Bobbin Phenolic
Wire Copper
Core Ferrite
Glue Epoxy

Contact Information

www.bourns.com	Phone	Email
Asia-Pacific	+886-2 2562-4117	asiacus@bourns.com
Europe	+36 88 885 877	eurocus@bourns.com
Mexico	+52 614 478 0400	mexicus@bourns.com
The Americas	+1-951 781-5500	americus@bourns.com

* RoHS Directive 2015/863, Mar 31, 2015 and Annex.
Specifications are subject to change without notice.
Users should verify actual device performance in their specific applications.

The products described herein and this document are subject to specific legal disclaimers as set forth on the last page of this document, and at www.bourns.com/docs/legal/disclaimer.pdf.


PKSEP6 SERIES

SMD Transformer for Ultrasonic Sensors




*RoHS COMPLIANT
& AEC-Q200 COMPLIANT


Product Dimensions



Recommended Layout



Electrical Schematic



How to Order

PKS EP6 A 08 S

Series _____
 Core Size _____
 Sub-series _____
 Turns Ratio N_s/N_p _____
 PCB Type _____


PKS = Parking Sensor
 EP6 = EP 6
 A = A
 B = B
 08 = Turns Ratio N_s/N_p 1:1:8.42 or 1:1:7.9
 09 = Turns Ratio N_s/N_p 1:1:9
 10 = Turns Ratio N_s/N_p 1:1:10.1
 15 = Turns Ratio N_s/N_p 1:1:15
 S = SMD

Specifications are subject to change without notice.
 Users should verify actual device performance in their specific applications.

The products described herein and this document are subject to specific legal disclaimers as set forth on the last page of this document, and at www.bourns.com/docs/legal/disclaimer.pdf.


PKSEP6 SERIES

SMD Transformer for Ultrasonic Sensors



*RoHS COMPLIANT
& AEC-Q200 COMPLIANT

Lead-free Soldering Profile



Profile Feature	Pb-Free Assembly
Preheat / Soak: Temperature Min. (T_{smin}) Temperature Max. (T_{smax}) Time (t_s) from (T_{smin} to T_{smax})	150 °C 200 °C 60~120 seconds
Ramp Up Rate (T_L to T_p)	3 °C / second max.
Liquidous Temperature (T_L) Time (t_L) maintained above T_L	217 °C 60~150 seconds
Peak Package Body Temperature (T_p)	$T_p \leq T_c$ (see table below)
Time (t_p)* within 5 °C of the specified classification temperature (T_c)	< 30 seconds*
Ramp Down Rate (T_p to T_L)	6 °C / second max.
Time 25 °C to Peak Temperature	8 minutes max.

Pb-Free Process Classification Temperatures (T_c)

Package Thickness	Volume mm ³ < 350	Volume mm ³ 350 - 2000	Volume mm ³ > 2000
< 1.6 mm	260 °C	260 °C	260 °C
1.6 mm - 2.5 mm	260 °C	250 °C	245 °C
> 2.5 mm	250 °C	245 °C	245 °C

NOTE: The product has been tested under this reflow condition. Deviations from this, especially higher temperatures for longer duration, could impact performance.


Refer to IPC/JEDEC J-STD-020

Specifications are subject to change without notice.
Users should verify actual device performance in their specific applications.

The products described herein and this document are subject to specific legal disclaimers as set forth on the last page of this document, and at www.bourns.com/docs/legal/disclaimer.pdf.

PKSEP6 SERIES


SMD Transformer for Ultrasonic Sensors



***RoHS COMPLIANT
& AEC-Q200 COMPLIANT**

Packaging Specifications

1000 pieces per reel, 5 reels per carton.



REV. 11/25

Specifications are subject to change without notice.
Users should verify actual device performance in their specific applications.

The products described herein and this document are subject to specific legal disclaimers as set forth on the last page of this document, and at www.bourns.com/docs/legal/disclaimer.pdf.

This legal disclaimer applies to purchasers and users of Bourns® products manufactured by or on behalf of Bourns, Inc. and its affiliates (collectively, "Bourns").

Unless otherwise expressly indicated in writing, Bourns® products and data sheets relating thereto are subject to change without notice. Users should check for and obtain the latest relevant information and verify that such information is current and complete before placing orders for Bourns® products.

The characteristics and parameters of a Bourns® product set forth in its data sheet are based on laboratory conditions, and statements regarding the suitability of products for certain types of applications are based on Bourns' knowledge of typical requirements in generic applications. The characteristics and parameters of a Bourns® product in a user application may vary from the data sheet characteristics and parameters due to (i) the combination of the Bourns® product with other components in the user's application, or (ii) the environment of the user application itself. The characteristics and parameters of a Bourns® product also can and do vary in different applications and actual performance may vary over time. Users should always verify the actual performance of the Bourns® product in their specific devices and applications, and make their own independent judgments regarding the amount of additional test margin to design into their device or application to compensate for differences between laboratory and real world conditions.

Unless Bourns has explicitly designated an individual Bourns® product as meeting the requirements of a particular industry standard (e.g., ISO/TS 16949) or a particular qualification (e.g., UL listed or recognized), Bourns is not responsible for any failure of an individual Bourns® product to meet the requirements of such industry standard or particular qualification. Users of Bourns® products are responsible for ensuring compliance with safety-related requirements and standards applicable to their devices or applications.

Bourns® products are not recommended, authorized or intended for use in nuclear, lifesaving, life-critical or life-sustaining applications, nor in any other applications where failure or malfunction may result in personal injury, death, or severe property or environmental damage. Unless expressly and specifically approved in writing by two authorized Bourns representatives on a case-by-case basis, use of any Bourns® products in such unauthorized applications might not be safe and thus is at the user's sole risk. Life-critical applications include devices identified by the U.S. Food and Drug Administration as Class III devices and generally equivalent classifications outside of the United States.

Bourns expressly identifies those Bourns® standard products that are suitable for use in automotive applications on such products' data sheets in the section entitled "Applications." Unless expressly and specifically approved in writing by two authorized Bourns representatives on a case-by-case basis, use of any other Bourns® standard products in an automotive application might not be safe and thus is not recommended, authorized or intended and is at the user's sole risk. If Bourns expressly identifies a sub-category of automotive application in the data sheet for its standard products (such as infotainment or lighting), such identification means that Bourns has reviewed

its standard product and has determined that if such Bourns® standard product is considered for potential use in automotive applications, it should only be used in such sub-category of automotive applications. Any reference to Bourns® standard product in the data sheet as compliant with the AEC-Q standard or "automotive grade" does not by itself mean that Bourns has approved such product for use in an automotive application.

Bourns® standard products are not tested to comply with United States Federal Aviation Administration standards generally or any other generally equivalent governmental organization standard applicable to products designed or manufactured for use in aircraft or space applications. Bourns expressly identifies Bourns® standard products that are suitable for use in aircraft or space applications on such products' data sheets in the section entitled "Applications." Unless expressly and specifically approved in writing by two authorized Bourns representatives on a case-by-case basis, use of any other Bourns® standard product in an aircraft or space application might not be safe and thus is not recommended, authorized or intended and is at the user's sole risk.

The use and level of testing applicable to Bourns® custom products shall be negotiated on a case-by-case basis by Bourns and the user for which such Bourns® custom products are specially designed. Absent a written agreement between Bourns and the user regarding the use and level of such testing, the above provisions applicable to Bourns® standard products shall also apply to such Bourns® custom products.

Users shall not sell, transfer, export or re-export any Bourns® products or technology for use in activities which involve the design, development, production, use or stockpiling of nuclear, chemical or biological weapons or missiles, nor shall they use Bourns® products or technology in any facility which engages in activities relating to such devices. The foregoing restrictions apply to all uses and applications that violate national or international prohibitions, including embargos or international regulations. Further, Bourns® products and Bourns technology and technical data may not under any circumstance be exported or re-exported to countries subject to international sanctions or embargoes. Bourns® products may not, without prior authorization from Bourns and/or the U.S. Government, be resold, transferred, or re-exported to any party not eligible to receive U.S. commodities, software, and technical data.

To the maximum extent permitted by applicable law, Bourns disclaims (i) any and all liability for special, punitive, consequential, incidental or indirect damages or lost revenues or lost profits, and (ii) any and all implied warranties, including implied warranties of fitness for particular purpose, non-infringement and merchantability.

For your convenience, copies of this Legal Disclaimer Notice with German, Spanish, Japanese, Traditional Chinese and Simplified Chinese bilingual versions are available at:

Web Page: <http://www.bourns.com/legal/disclaimers-terms-and-policies>

PDF: <http://www.bourns.com/docs/Legal/disclaimer.pdf>

