


40 A 1200 V automotive grade thyristor (SCR)



Features

- AEC-Q101 qualified 
- High junction temperature: 150 °C
- AC off state voltage: +/- 1200 V
- Nominal on-state RMS current: 40 A_{RMS}
- High EFT noise immunity: 1000 V/μs
- Max. gate triggering current: 50 mA
- **ECOPACK2** compliant component

Application

- On board charger
- Capacitor discharge
- Overvoltage crowbar protection
- Power supplies
- AC switches
- Solid state relays

Description

The **TN4050HP-12L2Y** is an automotive grade SCR thyristor designed for applications such as automotive on board and stationary battery chargers.

This SCR Thyristor, rated for a 40 A RMS power switching, offers superior performances in peak voltage robustness up to 400 V sine wave pulse. Its key features allow the design of functions such as a 56 A RMS AC switch and a 50 A AC-DC controlled rectifier-bridge.

Available in HU3PAK package, it is ideal for compact SMD designs on surface mount boards or insulated metal substrate boards and and top-side cooling.

Product status

TN4050HP-12L2Y

Product summary

I_{T(RMS)}	40 A
V_{DRM}/V_{RRM}	1200 V
V_{DSM}/V_{RSM}	1400 V
I_{GT}	50 mA
T_j	-40 to 150 °C

1 Characteristics

Table 1. Absolute ratings (limiting values)

Symbol	Parameter		Value	Unit
$I_{T(RMS)}$	RMS on-state current (180 ° conduction angle)	$T_C = 135\text{ °C}$	40	A
$I_{T(AV)}$	Average on-state current (180 ° conduction angle)		25	
I_{TSM}	Non repetitive surge peak on-state current, $V_R = 0\text{ V}$	$t_p = 8.3\text{ ms}$	440	A
		$t_p = 10\text{ ms}$	400	
I^2t	I^2t value for fusing	$t_p = 10\text{ ms}$	$T_j = 25\text{ °C}$	A^2s
di/dt	Critical rate of rise of on-state current, $I_G = 2 \times I_{GT}$, $tr \leq 100\text{ ns}$	$f = 50\text{ Hz}$	$T_j = 150\text{ °C}$	$A/\mu s$
V_{DRM} / V_{RRM}	Repetitive off-state voltage		$T_j = 150\text{ °C}$	V
V_{DSM} / V_{RSM}	Non repetitive surge peak off-state voltage	$t_p = 10\text{ ms}$	$T_j = 25\text{ °C}$	V
V_{GM}	Peak forward gate voltage	$t_p = 20\text{ }\mu s$	$T_j = 150\text{ °C}$	V
I_{GM}	Peak forward gate current	$t_p = 20\text{ }\mu s$	$T_j = 150\text{ °C}$	A
V_{RGM}	Maximum peak reverse gate voltage		$T_j = 25\text{ °C}$	V
$P_{G(AV)}$	Average gate power dissipation		$T_j = 150\text{ °C}$	W
T_{stg}	Storage junction temperature range		-40 to +150	°C
T_j	Operating junction temperature		-40 to +150	°C

Table 2. Electrical characteristics ($T_j = 25\text{ °C}$ unless otherwise specified)

Symbol	Test Conditions		Value	Unit
I_{GT}	$V_D = 12\text{ V}$, $R_L = 33\text{ }\Omega$	Min.	10	mA
		Max.	50	
V_{GT}		Max.	1.3	V
I_{GD}	$V_D = 800\text{ V}$, $R_L = 3.3\text{ }\Omega$	$T_j = 150\text{ °C}$	Min. 3	mA
V_{GD}	$V_D = 800\text{ V}$, $R_L = 3.3\text{ }\Omega$	$T_j = 150\text{ °C}$	Min. 0.2	V
I_H	$I_T = 500\text{ mA}$, gate open		Max. 100	mA
I_L	$I_G = 1.2 \times I_{GT}$		Max. 125	mA
dV/dt	$V_D = 800\text{ V}$, gate open	$T_j = 150\text{ °C}$	Min. 1000	$V/\mu s$

Table 3. Timing Parameters

Symbol	Test Conditions		Value	Unit
t_{gt}	$I_T = 80\text{ A}$, $V_D = 800\text{ V}$, $I_G = 100\text{ mA}$, $dI_G/dt = 0.2\text{ A}/\mu s$		Typ. 1	μs
t_q	$I_{TM} = 25\text{ A}$, $V_D = 800\text{ V}$, $dI_T/dt = 10\text{ A}/\mu s$, $V_R = 75\text{ V}$, $dV_D/dt = 20\text{ V}/\mu s$, $t_p = 100\text{ }\mu s$	$T_j = 150\text{ °C}$	Typ. 150	μs

Table 4. Static Characteristics

Symbol	Test Conditions			Value	Unit
V_{TM}	$I_{TM} = 80\text{ A}$, $t_P = 380\text{ }\mu\text{s}$	$T_j = 25\text{ }^\circ\text{C}$	Max.	1.55	V
V_{TO}	On-state threshold voltage	$T_j = 150\text{ }^\circ\text{C}$	Max.	0.83	V
R_D	On-state dynamic resistance	$T_j = 150\text{ }^\circ\text{C}$	Max.	10	m Ω
I_{DRM}/I_{RRM}	$V_D = V_{DRM}$, $V_R = V_{RRM}$	$T_j = 25\text{ }^\circ\text{C}$	Max.	5	μA
		$T_j = 125\text{ }^\circ\text{C}$		0.9	mA
		$T_j = 150\text{ }^\circ\text{C}$		6	mA
I_{DSM}/I_{RSM}	$V_D = V_{DSM}$, $V_R = V_{RSM}$	$T_j = 25\text{ }^\circ\text{C}$	Max.	10	μA

Table 5. Thermal parameters

Symbol	Parameter	Value	Unit
$R_{th(j-c)}$	Junction to case (DC)	Max.	0.4 $^\circ\text{C/W}$

1.1 Characteristics (curves)

Figure 1. Maximum average power dissipation versus average on-state current




Figure 2. Average and D.C. on-state current versus case temperature




Figure 3. Average and D.C. on-state current versus ambient temperature




Figure 4. On-state characteristics (maximum values)




Figure 5. Surge peak on-state current versus number of cycles




Figure 6. Non repetitive surge peak on-state current for a sinusoidal pulse with width $t_p < 10$ ms




Figure 7. Relative variation of leakage current versus junction temperature for different values of blocking voltage (typical values)




Figure 8. Relative variation of holding and latching current versus junction temperature (typical values)




Figure 9. Relative variation of gate trigger current and gate voltage versus junction temperature (typical values)




Figure 10. Relative variation of thermal impedance junction to case versus pulse duration





Figure 11. Relative variation of static dV/dt immunity versus junction temperature




2 Package information

To meet environmental requirements, ST offers these devices in different grades of **ECOPACK** packages, depending on their level of environmental compliance. ECOPACK specifications, grade definitions, and product status are available at: www.st.com. ECOPACK is an ST trademark.

2.1 HU3PAK package information

- Epoxy meets UL94, V0

Figure 12. HU3PAK package outline



DM00674007_2


Note: This package drawing may slightly differ from the physical package. However, all the specified dimensions are guaranteed.

Table 6. HU3PAK package mechanical data

Ref.	Dimensions		
	mm		
	Min.	Typ.	Max.
A	3.40	3.50	3.60
A1		0.05	
b	0.50	0.60	0.70
b2	0.50	0.70	1.00
b3	0.80	0.90	1.00
c	0.40	0.50	0.60
c2	0.40	0.50	0.60
D	11.70	11.80	11.90
D1	8.80	8.955	9.10
E	13.90	14.00	14.10
E1	12.30	12.40	12.50
E2	7.75	7.80	7.85
e	BSC 1.27		
H	18.00	18.58	19.00
L	2.40	2.52	2.60
L1		3.05	
L2	0.90	1.00	1.10
L3	BSC 0.26		
L4	0.075	0.125	0.175
L5	1.83	1.93	2.03
L6	2.14	2.24	2.34
L7	4.44	4.54	4.64
aaa		0.10	
F1	2.90	3.00	3.10
F2	2.40	2.50	2.60
F3	0.25	0.35	0.45
N1	3.80	3.90	4.00
N2	0.25	0.30	0.45
N3	0.80	0.90	1.00
T	0.50	0.67	0.70
T2	9.18	9.38	9.43
θ1		0°	8°
θ2		0°	8°

1. Package outline exclusive of any mold flashes dimensions.
2. Package outline exclusive of burr dimensions.
3. Max resin gate protrusion: 0.25 mm.
4. The planarity of the package backside 50 micron max.
5. BSC: basic spacing between centers

Figure 13. HU3PAK recommended footprint (dimensions are in mm)



DM00674007_2

Note: For packing details you can see technical note [TN1173: Packing information for IPAD, protection, rectifiers, thyristors and AC Switches](#).

2.2 HU³PAK packing information

Figure 14. HU³PAK carrier tape outline




Table 7. HU³PAK tape and reel mechanical data

Tape	
Dim.	mm
	Value
A0	14.40 ±0.1
B0	19.70
D	1.50 ±0.1
E	1.75 ±0.1
F	15.65 ±0.1
I0	11.00
I1	11.60 ±0.1
I2	8.0
I3	7.0
K0	4.20
P0	4.00 ±0.1
P1	20.00 ±0.1
P2	2.00 ±0.1
T	0.40 ±0.5
W	32.00 ±0.3

3 Ordering information

Figure 15. Ordering information scheme




Table 8. Ordering information

Order code	Marking	Package	Weight	Base qty.	Delivery mode
TN4050HP-12L2Y	TN4050HP12Y	HU ³ PAK	2.32 g	600	Tape and reel 13"

Revision history

Table 9. Document revision history

Date	Revision	Changes
08-Dec-2022	1	Initial release.
27-May-2024	2	Updated Table 5. Thermal parameters with $R_{th(j-c)}$ value.
22-Oct-2025	3	Updated Section 3: Ordering information .

IMPORTANT NOTICE – READ CAREFULLY

STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice.

In the event of any conflict between the provisions of this document and the provisions of any contractual arrangement in force between the purchasers and ST, the provisions of such contractual arrangement shall prevail.

The purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST's terms and conditions of sale in place at the time of order acknowledgment.

The purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of the purchasers' products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

If the purchasers identify an ST product that meets their functional and performance requirements but that is not designated for the purchasers' market segment, the purchasers shall contact ST for more information.

ST and the ST logo are trademarks of ST. For additional information about ST trademarks, refer to www.st.com/trademarks. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2025 STMicroelectronics – All rights reserved