



- Features:**
- 7/8" screw connection: Industry-proven connection technology for a large selection of different conductors
 - High protection class for safe field applications
 - Vibration- and shock-resistant via integrated locking mechanism
 - PUR coating

Technical data

Operating data	
Operating voltage	600 VAC/VDC
Operating current	9 A

Safety and protection

Rated impulse withstand voltage	4 kV
Protection type	IP67

Connection data

Connection 1	
Connection technology	7/8"; 3-pole; straight socket

Material data

Fire load	0 MJ
Weight	40 g



Environmental requirements		
Ambient temperature (operation)		-25 ... +80 °C

Commercial data		
PU (SPU)		1 pcs
Packaging type		Bag
Country of origin		DE
GTIN		4055143726900
Customs tariff number		85366990990

Product Classification		
UNSPSC		39121402
ETIM 9.0		EC002635
ETIM 8.0		EC002635
ECCN		NO US CLASSIFICATION

Environmental Product Compliance		
RoHS Compliance Status		Compliant,No Exemption

Downloads		
Environmental Product Compliance		
Compliance Search		
Environmental Product Compliance		↓
787-6716/9300-000		

Documentation				
Bid Text				
787-6716/9300-0000	19.02.2019	xml	3.38 KB	↓
787-6716/9300-000	12.06.2019	docx	16.74 KB	↓
787-6716/9300-000	12.06.2019	pdf	65.19 KB	↓
787-6716/9300-0000	13.08.2018	doc	30.00 KB	↓

Subject to changes. Please also observe the further product documentation!

Current addresses can be found at: www.wago.com