


Item no.: 858-314
Product description: 4 CHANGEOVER CONTACTS (GOLD CONTACTS)



Produkt kann von Bild abweichen / product may differ

Packing unit 1 piece

RoHS compliant

Coil voltage DC	24 V
Coil current	36.9 mA
Continuous current	50 mA
1-phase motor load AC3	0.12 kW
Pull-in time (typ)	25 ms
Drop-out time (typ)	25 ms
Bounce time (typ)	4 ms
Dielectric strength contact / coil (1,2/50 µs)	4 kV
Dielectric strength contact-coil (AC, 1 min)	1.5 kV
Dielectric strength open contact	1 kV
Dielectric strength contact-contact	1.5 kV
Cross section [mm²]	0.34 - 1.5 mm²
Cross section [AWG]	22 - 16 AWG
Connection method	CAGE CLAMP®S Connection
Weight	96.717 g
Height	73 mm
Height	2.874 in
Width	31 mm
Width	1.22 in

Depth	97 mm
Depth	3.819 in
Strip length from	9 mm



Strip length to	10 mm
Strip length	0.37 in
Customs Tariff No.	85369010
Country of Origin	Deutschland

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected