M4/8.SF



Extended Product Type:	M4/8.SF
Product ID:	1SNA115657R2500
EAN:	3472591156577
Catalog Description:	M4/8.SF
Long Description:	M4/8.SF Screw Clamp Terminal Blocks Fuse
Long Description.	
ategories	
Products » Low Voltage Products an	d Systems » Connection Devices » Terminal Blocks » Screw Clamp Terminal Blocks
) - do vio a	
Drdering	0.17050.1150577
EAN:	3472591156577
Minimum Order Quantity:	50 piece
Customs Tariff Number:	85369010
Dimensions	
Product Net Weight:	13 g
Container Information	50 pices
Package Level 1 Units:	50 piece
Package Level 1 Width:	101 mm
Package Level 1 Height:	47 mm
Package Level 1 Length:	265 mm
Package Level 1 Gross Weight:	0.65 kg
Package Level 1 EAN:	3472591156577
Package Level 2 Units:	450 piece
Package Level 2 Width:	300 mm
Package Level 2 Height:	150 mm
Package Level 2 Length:	500 mm
Package Level 2 Gross Weight:	6.2 kg
Product Packing Type: Environmental	6.2 kg Box Following EU Directive 2002/95/EC August 18, 2005 and amendment
Product Packing Type: Environmental RoHS Status:	Box
Product Packing Type: Environmental RoHS Status: Fechnical UL/CSA	Box
Product Packing Type: Environmental RoHS Status: echnical UL/CSA Flammability According to UL94:	Box Following EU Directive 2002/95/EC August 18, 2005 and amendment
Product Packing Type: Environmental RoHS Status: Technical UL/CSA Flammability According to UL94: Additional Information	Box Following EU Directive 2002/95/EC August 18, 2005 and amendment V0
Product Packing Type: Environmental RoHS Status: Echnical UL/CSA Flammability According to UL94: Additional Information Color:	Box Following EU Directive 2002/95/EC August 18, 2005 and amendment V0 grey
Product Packing Type: Environmental RoHS Status: Echnical UL/CSA Flammability According to UL94: Additional Information Color: Connection Type:	Box Following EU Directive 2002/95/EC August 18, 2005 and amendment V0 grey Screw clamp
Product Packing Type: Environmental RoHS Status: Technical UL/CSA Flammability According to UL94: Additional Information Color: Connection Type: Function:	Box Following EU Directive 2002/95/EC August 18, 2005 and amendment V0 grey grey Screw clamp Fuse
Product Packing Type: Environmental RoHS Status: Technical UL/CSA Flammability According to UL94: Additional Information Color: Connection Type: Function: IT Publishing Status:	Box Following EU Directive 2002/95/EC August 18, 2005 and amendment V0 grey grey Screw clamp Fuse Level 0 - Information enabled
Product Packing Type: Environmental RoHS Status: Technical UL/CSA Flammability According to UL94: Additional Information Color: Connection Type: Function: IIT Publishing Status: Pollution Degree:	Box Following EU Directive 2002/95/EC August 18, 2005 and amendment V0 V0 grey Screw clamp Fuse Level 0 - Information enabled 3
Product Packing Type: Environmental RoHS Status: Fechnical UL/CSA Flammability According to UL94: Additional Information Color: Connection Type: Function: IT Publishing Status: Pollution Degree: Product Main Type:	Box Following EU Directive 2002/95/EC August 18, 2005 and amendment V0 V0 grey Screw clamp Fuse Level 0 - Information enabled 3 M4/8.SF
Product Packing Type: Environmental RoHS Status: Technical UL/CSA Flammability According to UL94: Additional Information Color: Connection Type: Function: IT Publishing Status: Pollution Degree: Product Main Type: Product Name:	Box Following EU Directive 2002/95/EC August 18, 2005 and amendment V0 V0 grey Screw clamp Fuse Level 0 - Information enabled 3 M4/8.SF Terminal block
Product Packing Type: Environmental RoHS Status: Technical UL/CSA Flammability According to UL94: Additional Information Color: Connection Type: Function: IT Publishing Status: Pollution Degree: Product Main Type: Product Name: Rated Cross-Section:	Box Following EU Directive 2002/95/EC August 18, 2005 and amendment V0 V0 grey Screw clamp Fuse Level 0 - Information enabled 3 M4/8.SF Terminal block 4 mm ²
Product Packing Type: Environmental RoHS Status: Technical UL/CSA Flammability According to UL94: Additional Information Color: Connection Type: Function: IT Publishing Status: Pollution Degree: Product Main Type: Product Name: Rated Cross-Section: Rated Impulse Withstand Voltage	Box Following EU Directive 2002/95/EC August 18, 2005 and amendment V0 V0 grey Screw clamp Fuse Level 0 - Information enabled 3 M4/8.SF Terminal block
Product Packing Type: Environmental RoHS Status: Technical UL/CSA Flammability According to UL94: Additional Information Color: Connection Type: Function: IT Publishing Status: Pollution Degree: Product Main Type: Product Name: Rated Cross-Section: Rated Impulse Withstand Voltage (U _{imp}):	Box Following EU Directive 2002/95/EC August 18, 2005 and amendment V0 V0 grey Screw clamp Fuse Level 0 - Information enabled 3 M4/8.SF Terminal block 4 mm ²
Product Packing Type: Environmental RoHS Status: Technical UL/CSA Flammability According to UL94: Additional Information Color: Connection Type: Function: IIT Publishing Status: Pollution Degree: Product Main Type: Product Name: Rated Cross-Section: Rated Impulse Withstand Voltage (U _{imp}): Recommended Screw Driver:	Box Following EU Directive 2002/95/EC August 18, 2005 and amendment V0 V0 grey Screw clamp Fuse Level 0 - Information enabled 3 M4/8.SF Terminal block 4 mm ² 8 kV 4 mm
Product Packing Type: Environmental RoHS Status: Technical UL/CSA Flammability According to UL94: Additional Information Color: Connection Type: Function: IT Publishing Status: Pollution Degree: Product Main Type: Product Main Type: Product Name: Rated Cross-Section: Rated Impulse Withstand Voltage (U _{imp}): Recommended Screw Driver: Spacing:	Box Following EU Directive 2002/95/EC August 18, 2005 and amendment V0 V0 grey Screw clamp Fuse Level 0 - Information enabled 3 M4/8.SF Terminal block 4 mm² 8 kV
Product Packing Type: Environmental RoHS Status: Technical UL/CSA Flammability According to UL94: Additional Information Color: Connection Type: Function: IT Publishing Status: Pollution Degree: Product Main Type: Product Main Type: Product Name: Rated Cross-Section: Rated Impulse Withstand Voltage U _{imp}): Recommended Screw Driver: Spacing: Sub-Function:	Box Following EU Directive 2002/95/EC August 18, 2005 and amendment V0 V0 grey Screw clamp Fuse Level 0 - Information enabled 3 M4/8.SF Terminal block 4 mm ² 8 kV 4 mm 8 mm for 5x2 and 5x25 Fuses
Product Packing Type: Environmental RoHS Status: Technical UL/CSA Flammability According to UL94: Additional Information Color: Connection Type: Function: IT Publishing Status: Pollution Degree: Product Main Type: Product Main Type: Product Name: Rated Cross-Section: Rated Impulse Withstand Voltage [U _{imp}): Recommended Screw Driver: Spacing: Sub-Function:	Box Following EU Directive 2002/95/EC August 18, 2005 and amendment V0 V0 grey Screw clamp Fuse Level 0 - Information enabled 3 M4/8.SF Terminal block 4 mm² 8 kV
Product Packing Type: Environmental RoHS Status: Fechnical UL/CSA Flammability According to UL94: Additional Information Color: Connection Type: Function: IIT Publishing Status: Pollution Degree: Product Main Type: Product Main Type: Product Name: Rated Cross-Section: Rated Impulse Withstand Voltage [U _{imp}): Recommended Screw Driver: Spacing: Sub-Function: Tightening Torques:	Box Following EU Directive 2002/95/EC August 18, 2005 and amendment V0 V0 grey Screw clamp Fuse Level 0 - Information enabled 3 M4/8.SF Terminal block 4 mm ² 8 kV 4 mm 8 mm for 5x2 and 5x25 Fuses acc. IEC 60947-1 0.5 Nm
Product Packing Type: Environmental RoHS Status: Technical UL/CSA Flammability According to UL94: Additional Information Color: Connection Type: Function: IIT Publishing Status: Pollution Degree: Product Main Type: Product Main Type: Product Name: Rated Cross-Section: Rated Impulse Withstand Voltage (U _{imp}): Recommended Screw Driver: Spacing: Sub-Function: Tightening Torques: Wire Stripping Length:	Box Following EU Directive 2002/95/EC August 18, 2005 and amendment V0 grey Screw clamp Fuse Level 0 - Information enabled 3 M4/8.SF Terminal block 4 mm² 8 kV 4 mm 8 mm for 5x2 and 5x25 Fuses acc. IEC 60947-1 0.5 N·m Manufacturer 0.8 N·m 9.5 mm
Product Packing Type: Environmental RoHS Status: Technical UL/CSA Flammability According to UL94: Additional Information Color: Connection Type: Function: IIT Publishing Status: Pollution Degree: Product Main Type: Product Name: Rated Cross-Section: Rated Impulse Withstand Voltage (U _{imp}): Recommended Screw Driver: Spacing: Sub-Function: Tightening Torques: Wire Stripping Length: Certificates and Declarations (D	Box Following EU Directive 2002/95/EC August 18, 2005 and amendment V0 grey Screw clamp Fuse Level 0 - Information enabled 3 M4/8.SF Terminal block 4 mm² 8 kV 4 mm² 8 mm for 5x2 and 5x25 Fuses acc. IEC 60947-1 0.5 N·m Manufacturer 0.8 N·m 9.5 mm
Product Packing Type: Environmental RoHS Status: <u>Fechnical UL/CSA</u> Flammability According to UL94: Additional Information Color: Connection Type: Function: IIT Publishing Status: Pollution Degree: Product Main Type: Product Main Type: Product Name: Rated Cross-Section: Rated Cross-Section: Rated Impulse Withstand Voltage (U _{imp}): Recommended Screw Driver: Spacing: Sub-Function: Tightening Torques: Wire Stripping Length: <u>Certificates and Declarations (D</u> Declaration of Conformity - CE:	Box Following EU Directive 2002/95/EC August 18, 2005 and amendment V0 grey Screw clamp Fuse Level 0 - Information enabled 3 M4/8.SF Terminal block 4 mm² 8 kV 4 mm 8 mm for 5x2 and 5x25 Fuses acc. IEC 60947-1 0.5 N·m Manufacturer 0.8 N·m 9.5 mm
Package Level 2 Gross Weight: Product Packing Type: Environmental RoHS Status: Fechnical UL/CSA Flammability According to UL94: Additional Information Color: Connection Type: Function: IIT Publishing Status: Pollution Degree: Product Main Type: Product Name: Rated Cross-Section: Rated Cross-Section: Rated Impulse Withstand Voltage (U _{imp}): Recommended Screw Driver: Spacing: Sub-Function: Tightening Torques: Wire Stripping Length: Certificates and Declarations (D Declaration of Conformity - CE: GOST Certificate:	Box Following EU Directive 2002/95/EC August 18, 2005 and amendment V0 grey Screw clamp Fuse Level 0 - Information enabled 3 M4/8.SF Terminal block 4 mm² 8 kV 4 mm 8 mm for 5x2 and 5x25 Fuses acc. IEC 60947-1 0.5 N·m Manufacturer 0.8 N·m 9.5 mm
Product Packing Type: Environmental RoHS Status: Fechnical UL/CSA Flammability According to UL94: Additional Information Color: Connection Type: Function: IIT Publishing Status: Pollution Degree: Product Main Type: Product Name: Rated Cross-Section: Rated Impulse Withstand Voltage (U _{imp}): Recommended Screw Driver: Spacing: Sub-Function: Tightening Torques: Wire Stripping Length: Certificates and Declarations (D Declaration of Conformity - CE: GOST Certificate: Classifications	Box Following EU Directive 2002/95/EC August 18, 2005 and amendment V0 grey Screw clamp Fuse Level 0 - Information enabled 3 M4/8.SF Terminal block 4 mm ² 8 kV 4 mm 8 mm for 5x2 and 5x25 Fuses acc. IEC 60947-1 0.5 N·m Manufacturer 0.8 N·m 9.5 mm Forcument Number) SND225007C1000 1SND161005A1103
Product Packing Type: Environmental RoHS Status: Technical UL/CSA Flammability According to UL94: Additional Information Color: Connection Type: Function: IIT Publishing Status: Pollution Degree: Product Main Type: Product Name: Rated Cross-Section: Rated Impulse Withstand Voltage (U _{imp}): Recommended Screw Driver: Spacing: Sub-Function: Tightening Torques: Wire Stripping Length: Certificates and Declarations (D Declaration of Conformity - CE:	Box Following EU Directive 2002/95/EC August 18, 2005 and amendment V0 grey Screw clamp Fuse Level 0 - Information enabled 3 M4/8.SF Terminal block 4 mm² 8 kV 4 mm 8 mm for 5x2 and 5x25 Fuses acc. IEC 60947-1 0.5 N·m Manufacturer 0.8 N·m 9.5 mm

