

ML SERIES

105°C 5mm~9mm Height, Long Life

*Load Life : 105°C 3000~5000 hours.

RoHS
compliance



◆SPECIFICATIONS

Items	Characteristics																																	
Category Temperature Range	-40~+105℃																																	
Rated Voltage Range	6.3~50Vdc																																	
Capacitance Tolerance	±20% (20℃,120Hz)																																	
Leakage Current(MAX)	I=0.01CV or 3μA whichever is greater.(After 2 minutes application of rated voltage) I=Leakage Current(μA) C=Capacitance(μF) V=Rated Voltage(Vdc)																																	
Dissipation Factor(MAX) (tanδ)	<table><tr><td>Rated Voltage (V)</td><td>6.3</td><td>10</td><td>16</td><td>25</td><td>35</td><td>50</td></tr><tr><td>tanδ</td><td>0.40</td><td>0.35</td><td>0.30</td><td>0.25</td><td>0.20</td><td>0.20</td></tr></table> (20℃,120Hz)							Rated Voltage (V)	6.3	10	16	25	35	50	tanδ	0.40	0.35	0.30	0.25	0.20	0.20													
Rated Voltage (V)	6.3	10	16	25	35	50																												
tanδ	0.40	0.35	0.30	0.25	0.20	0.20																												
Endurance	After applying rated voltage with rated ripple current for specified time at 105℃, the capacitors shall meet the following requirements. <table><tr><td>Capacitance Change</td><td colspan="5">Within ±30% of the initial value.</td><td><table><tr><td>Case Size</td><td>Life Time (hrs)</td></tr><tr><td>L=5mm</td><td>3000</td></tr><tr><td>L≥7mm</td><td>5000</td></tr></table></td></tr><tr><td>Dissipation Factor</td><td colspan="5">Not more than 300% of the specified value.</td><td></td></tr><tr><td>Leakage Current</td><td colspan="5">Not more than the specified value.</td><td></td></tr></table>							Capacitance Change	Within ±30% of the initial value.					<table><tr><td>Case Size</td><td>Life Time (hrs)</td></tr><tr><td>L=5mm</td><td>3000</td></tr><tr><td>L≥7mm</td><td>5000</td></tr></table>	Case Size	Life Time (hrs)	L=5mm	3000	L≥7mm	5000	Dissipation Factor	Not more than 300% of the specified value.						Leakage Current	Not more than the specified value.					
Capacitance Change	Within ±30% of the initial value.					<table><tr><td>Case Size</td><td>Life Time (hrs)</td></tr><tr><td>L=5mm</td><td>3000</td></tr><tr><td>L≥7mm</td><td>5000</td></tr></table>	Case Size	Life Time (hrs)	L=5mm	3000	L≥7mm	5000																						
Case Size	Life Time (hrs)																																	
L=5mm	3000																																	
L≥7mm	5000																																	
Dissipation Factor	Not more than 300% of the specified value.																																	
Leakage Current	Not more than the specified value.																																	
Low Temperature Stability Impedance Ratio(MAX)	<table><tr><td>Rated Voltage (Vdc)</td><td>6.3</td><td>10</td><td>16</td><td>25</td><td>35</td><td>50</td></tr><tr><td>Z(-25℃)/Z(20℃)</td><td>6</td><td>4</td><td>4</td><td>3</td><td>2</td><td>2</td></tr><tr><td>Z(-40℃)/Z(20℃)</td><td>12</td><td>10</td><td>8</td><td>6</td><td>4</td><td>4</td></tr></table> (120Hz)							Rated Voltage (Vdc)	6.3	10	16	25	35	50	Z(-25℃)/Z(20℃)	6	4	4	3	2	2	Z(-40℃)/Z(20℃)	12	10	8	6	4	4						
Rated Voltage (Vdc)	6.3	10	16	25	35	50																												
Z(-25℃)/Z(20℃)	6	4	4	3	2	2																												
Z(-40℃)/Z(20℃)	12	10	8	6	4	4																												

◆MULTIPLIER FOR RIPPLE CURRENT

Frequency (Hz)	60(50)	120	500	1k	10k≤
Coefficient					
1μF	0.50	1.00	1.20	1.30	1.50
2.2~6.8μF	0.65	1.00	1.20	1.30	1.50
10~82μF	0.80	1.00	1.20	1.30	1.50
100~1000μF	0.80	1.00	1.10	1.15	1.20

◆OPTION


	Code
PET Sleeve	EFC

◆PART NUMBER

□□□	ML	□□□□□	M	□□□	□□	DxL
Rated Voltage	Series	Capacitance	Capacitance Tolerance	Option	Lead Forming	Case Size

◆ DIMENSIONS

(mm)



ϕD	4	5	6.3	8×5	8×7	8×7.5	8×9	10
ϕd	0.45						0.6	
F	1.5	2.0	2.5		3.5			5.0
α	L=7 : α =1.0 L=5 : α =1.5			1.5	1.0		2.0	

◆ **STANDARD SIZE**

Size $\phi D \times L$ (mm), Rated Ripple Current (mA r.m.s./105°C, 120Hz)[illegible]