




File: E209153



ISO9001:2008 Certified

Mechanical Specifications (mm)

D:	16.0	± max
T:	6.0	± max
Lead Diameter	0.8	± nom
S:	7.8	± nom
L:	38.0	± nom
Coating Lead Run Down (straight Leads)	5.0	± max
B:	5.00	± nom
C:	3.45	± nom



Electrical Specifications

Resistance:	220.0 Ω	± 25 %
Max Steady State Current upto 65°C:	2.00	A
Max Rec. Energy Rating:	40	J
Actual Failure Instantaneous Energy:	80	J
Maximum Capacitance @ 120 VAC:	3,473	μ f
Maximum Capacitance @ 240 VAC:	868	μ f
Resistance @ 100% Max Current:	0.90	Ω
Resistance @ 50% Max Current:	1.90	Ω
Body Temperature at 100% Max Current:	191.00	°C
Dissipation Constant:	18.0	mw/°C
Thermal Time Constant:	45	Sec.
Material Type (for Beta and Curve):	L	

SL15 22102

Date: 07/15/2010

Drawn by: Erin Landis

Ametherm, Inc.
3111 N. Deer Run Road
Carson City, Nevada USA 89701
www.ametherm.com

Approved By: Mehdi Samii

Revision: a