




File: E209153



ISO9001:2008 Certified

Mechanical Specifications (mm)

D:	15.0	± .5
T:	4.5	± .2
Lead Diameter	0.8	± .1
S:	7.8	± 2
L:	38.0	± 9
Coating Lead Run Down (straight Leads)	5.0	± .5
B:	7.50	± .70
C:	2.82	± .5



Electrical Specifications

Resistance:	5.0	Ω	± 20 %
Max Steady State Current upto 65°C:	6.00	A	
Max Rec. Energy Rating:	50	J	
Actual Failure Instantaneous Energy:	75	J	
Maximum Capacitance @ 120 VAC:	3,400	μf	
Maximum Capacitance @ 240 VAC:	750	μf	
Resistance @ 100% Max Current:	0.12	Ω	
Resistance @ 50% Max Current:	0.24	Ω	
Body Temperature at 100% Max Current:	170.00	°c	
Dissipation Constant:	15.9	mw/°c	
Thermal Time Constant:	54	Sec.	
Material Type (for Beta and Curve):	C		

SL15 5R006

Date: 10/11/2012

Drawn by: Erin Landis

Ametherm, Inc.
3111 N. Deer Run Road
Carson City, Nevada USA 89701
www.ametherm.com

Approved By: Mehdi Samii

Revision: A