


# NCP18XW472J03RB

In Production Recommended RoHS REACH

## Appearance & Shape



## Features

1. Excellent solderability and high stability in environment
2. Excellent long time aging stability
3. High accuracy in resistance and B-constant
4. Flow / Reflow soldering possible
5. Same B-Constant in the same resistance in the three sizes (0805 size / 0603 size / 0402 size)
6. Easy to use smaller size in the circuits
7. Lead is not contained in the product.
7. NCP series are recognized by UL/cUL (UL 1434, File No.E137188).

## Applications

|             |                                                                       |
|-------------|-----------------------------------------------------------------------|
| Other Usage | 1. Temperature compensation for transistor, IC and crystal oscillator |
|-------------|-----------------------------------------------------------------------|

## Packaging Information

| Packaging | Specifications   | Minimum Order Quantity |
|-----------|------------------|------------------------|
| RB        | 180mm Paper Tape | 4000                   |

### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, its specifications are subject to change or our products may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.  
2. This datasheet has only typical specifications because there is no space for detailed specifications. Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

# NCP18XW472J03RB

## Specifications

|                                         |                |
|-----------------------------------------|----------------|
| Resistance (25°C)                       | 4.7kΩ          |
| Resistance Value Tolerance (at 25°C)    | ±5%            |
| B-Constant (25/50°C)                    | 3950K          |
| B-Constant (25/50°C) Tolerance          | ±3%            |
| B-Constant (25/80°C) (Reference Value)  | 3982K          |
| B-Constant (25/85°C) (Reference Value)  | 3987K          |
| B-Constant (25/100°C) (Reference Value) | 3998K          |
| Permissive Operating Current (25°C)     | 0.46mA         |
| Rated Electric Power (25°C)             | 100mW          |
| Typical Dissipation Constant (25°C)     | 1mW/°C         |
| Operating Temperature Range             | -40°C to 125°C |
| Shape                                   | SMD            |


### Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.  
2.This datasheet has only typical specifications because there is no space for detailed specifications.  
Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

# NCP18XW472J03RB



## Product Data



Resistance-Temperature Characteristics

### Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.  
2.This datasheet has only typical specifications because there is no space for detailed specifications.  
Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.