


CODE: **S116WP** v.1.0/1
 TYPE: **S116WP 16-port PoE switch for 16 IP cameras without power supply**

EN



Features:

- 16 ports switch
- 16 PoE ports 10/100 Mb/s (data and power supply)
- 2 ports 10/100/1000 Mb/s (G1/G2 ports) (UpLink)
- **Long Range** mode (up to 250m)
- 30W for each PoE port, supports devices compliant with the IEEE802.3af/at (**PoE+**) standard
- Supports auto-learning and auto-aging of MAC addresses (16K size)
- LED indication
- Additional assembly elements
- warranty – 2 years from production date

DESCRIPTION

S116WP is a 16-ports PoE switch designed to supply IP cameras operating in IEEE 802.3af/at standard. Automatic detection of any devices powered in the PoE/PoE+ standard is enabled at the 1 – 16 ports of the switch. The G1 and G2 ports is used for connection of another network device via RJ45 connector. The LEDs at the front panel indicate the operation status.

The PoE technology ensures a network connection and reduces installation costs by eliminating the need to supply a separate power cable for each device. This method allows supplying other network devices, such as IP phone, wireless access point or router.

TECHNICAL PARAMETERS

Ports	16 x PoE (10/100 Mb/s) (RJ-45) 2 x UpLink (10/100/1000 Mb/s) (RJ-45) with connection speed auto-negotiation and MDI/MDIX Auto Cross)
PoE power supply	IEEE 802.3af/at (1÷16 ports), 52 V DC / 30 W at each port *
Operating modes	Long Range, VLAN
Protocols, Standards	IEEE802.3, 802.3u, 802.3x CSMA/CD, TCP/IP
Bandwidth	14,8 Gb/s
Transmission method	Store-and-Forward
Optical indication of operation	Switch power supply; Link/Act; PoE Status
Power supply	48-54 V DC; 5 A max.
Operating conditions	temperature -10°C ÷ 40°C, relative humidity 5% - 90%, no condensation
Dimensions	W=270, H=44, D=181 [+/- 2mm]
Additional equipment	bracket for Rack 19"
Net/gross weight	1,25 / 1,45 [kg]
Protection class	I (first)
EN 60950-1:2007	
Storage temperatur	-20°C ÷ 60°C
Declarations, warranty	CE, 2 year from the production date

* The given value of 30 W per port is the maximum value. The total power consumption should not exceed 240 W when all PoE ports are being used.

Connection schemes

